



### Caractéristiques:

### Logistique

#### FUTURELIGHT DMH-90 LED Moving Head

High performance LED moving head with LUMINUS CBM-360 LED

- 1 extra bright LUMINUS CBM-360 LED for best luminance
- 16, 18 or 19 DMX channels selectable
- Effect wheel with rotating 3-facet prism and 8-facet prism and frost filter
- Color wheel with 8 different dichroic color filters plus white
- Rainbow effect with adjustable speed in both directions
- Gobo wheel with 7 rotating gobos plus open
- All gobos can be interchanged
- Slot-in gobo system for exchanging gobos without tools
- With gobo shake function
- Exact positioning via 16 bit PAN/TILT movement resolution
- Motorized focus
- Dimmer
- Strobe effect with adjustable speed
- Random strobe effect
- Automatic position correction
- PAN angle switchable between 540° and 630°
- Sound-controlled via built-in microphone
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector

- Control board with graphic LCD display and foil-keyboard for adjusting the DMX-starting address, PAN/TILT reverse, reset
- DMX-controlled operation or stand-alone operation with Master/Slave function
- The scenes can be modified via the Control Board or via an external controller and loaded into the memory
- Number of scenes can be changed individually
- Software upload by optional accessories via DMX link
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via any standard DMX controller
- Utilisable dans le mode CH DMX 16; 18; 19
- Commandé via commande de la musique via microphone; DMX; RDM

### ROADINGER Flightcase 2x DMH-90/DMH-150

PRO flightcase for 2 x FUTURELIGHT DMH-90/DMH-150 LED moving head

- Developed for 51841950 FUTURELIGHT DMH-90 LED Moving Head, 51841970 FUTURELIGHT DMH-150 LED Moving Head or comparable Moving Heads
- Suitable for 2 units
- Interior and cover upholstered with foam
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, medium-sized steel ball corners (chromium plated)
- 4 castors, 2 of which with locking brakes
- 2 high-quality butterfly locks
- 2 high-quality plated case handles
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

### Données techniques:

|        |          |
|--------|----------|
| Poids: | 56,00 kg |
|--------|----------|

### FUTURELIGHT DMH-90 LED Moving Head

|                                     |                                                              |
|-------------------------------------|--------------------------------------------------------------|
| Alimentation électrique:            | 100-240 V CA, 50/60 Hz                                       |
| Puissance totale de raccordement:   | 200 W                                                        |
| Mouvement de basculement max. TILT: | 270° positionnement                                          |
| Mouvement de pivotement max. PAN:   | 630° positionnement                                          |
| Gobos:                              | Diamètre externe 27mm<br>Diamètre de l'image 22mm            |
| Canaux DMX:                         | 16; 18; 19                                                   |
| Commande:                           | Commande de la musique via microphone; DMX; RDM              |
| Angle de départ (1/2 pic):          | 14°                                                          |
| Couleur:                            | Noir                                                         |
| Dimension:                          | Largeur : 34,3 cm<br>Profondeur : 25 cm<br>Hauteur : 42,8 cm |
| Poids:                              | 13,70 kg                                                     |
| DMX channels:                       | 16/18/19                                                     |
| DMX connection:                     | 3-pin XLR                                                    |

|                                |                              |
|--------------------------------|------------------------------|
| Sound-control:                 | via built-in microphone      |
| LED type:                      | LUMINUS CBM-360              |
| LED number:                    | 1                            |
| Beam angle:                    | 14°                          |
| Color-wheel:                   | 8 dichroic filters plus open |
| Rotating gobo-wheel:           | 7 gobos and open             |
| Outside diameter of the gobos: | 27 mm                        |
| Image diameter of the gobos:   | 22 mm                        |
| Maximum PAN-movement:          | 630°                         |
| Maximum TILT-movement:         | 270°                         |
| Dimensions (L x W x H):        | 343 x 250 x 428 mm           |

#### **ROADINGER Flightcase 2x DMH-90/DMH-150**

|                                 |                    |
|---------------------------------|--------------------|
| Charge maximale:                | 100 kg             |
| Strength:                       | 7 mm               |
| Outside dimensions (W x D x H): | 950 x 470 x 695 mm |
| Inside dimensions (W x D x H):  | 920 x 430 x 470 mm |
| Weight:                         | 30 kg              |

#### **Contenu de la livraison:**