



L'article n'est plus disponible.

Caractéristiques:

Logistique

EUROLITE PAR-56 Spot Long With PAR-Safe bk

Allrounder dans un boîtier long

- Rugged aluminum housing
- Strong aluminum mounting bracket with hole for fixing the obligatory safety rope
- Heat-resistant fixing screw for "bombproof" fixing
- The screw is protected against turning it too far out
- If the screw is loosened the spot remains in its position due to the brake
- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Safety grille (splinter protection) is integrated in the tube
- Internally blackened tube for precise light output
- Strong extension spring for safe hold and for quick opening of the rear housing cover
- Protection grille on the rear housing cover - complies with CE-regulations
- Comes fully-wired with black silicone cable, stable earthing in the housing and directly clamped ceramic socket
- Delivered with color filter frame
- With strong cable tension relief
- Well-suited for easy installation of our Raylight reflectors with matching connector (GX16)
- Simple mounting: connect with ceramic socket - ready!
- Power plug has to be ordered separately; delivery is with open cable ends
- Pour PAR 56

OMNILUX PAR-56 230 V / 300 W NSP 2000 h H

Ampoule spéciale pour effets lumineux

- Dimmable
- Indice de rendu de couleur (IRC) très élevé

Données techniques:

Poids:	1,86 kg
--------	---------

EUROLITE PAR-56 Spot Long With PAR-Safe bk

Alimentation électrique:	230 V AC, 50 Hz
--------------------------	-----------------

Puissance totale de raccordement:	500 W
-----------------------------------	-------

Couleur du boîtier:	Noir
---------------------	------

Dimension:	Largeur : 25 cm Profondeur : 30 cm Hauteur : 35 cm
------------	--

Poids:	1,30 kg
--------	---------

Dimensions (L x W x H):	350 x 250 x 300 mm
-------------------------	--------------------

OMNILUX PAR-56 230 V / 300 W NSP 2000 h H

Tension de service:	230 V
---------------------	-------

Tension nominale:	300 W
-------------------	-------

Culot/douille:	GX16d
----------------	-------

Type de lampe:	Lampe à incandescence; Lampe halogène; reflector lamp
----------------	---

Spécification de l'ampoule:	Dimmable
-----------------------------	----------

Angle de départ:	10°
------------------	-----

Couleur lumineuse:	Blanc
--------------------	-------

Température de couleur:	2800K
-------------------------	-------

Rendu de couleur (CRI):	99,3 Ra
-------------------------	---------

Durée de démarrage:	0,5 s
---------------------	-------

Construction:	PAR-56
---------------	--------

Température de fonctionnement max.:	40° C
-------------------------------------	-------

Température de fonctionnement min.:	20° C
-------------------------------------	-------

Position de fonctionnement:	S180 (universal)
-----------------------------	------------------

Durée de vie:	2000 h
---------------	--------

Flux lumineux:	3500 lm
----------------	---------

Longueur d'onde:	778 nm
------------------	--------

Dimensions (LxD):	127x178 mm
-------------------	------------

Poids:	0,56 kg
--------	---------

EPREL-Nr:	1273391
-----------	---------

Contenu de la livraison:
