EUROLITE Set 4x LED PIX-8 QCL Bar + MADRIX NEO - USB-DMX512-Interface

Réf. : 09000458

GTIN:





L'article n'est plus disponible.

Caractéristiques:

Logistique

EUROLITE LED PIX-8 QCL Bar

Compact LED color changing bar with 8 x 8 W 4in1 LED

- Equipped with eight QCL LEDs in the colors red, green, blue and white
- Particularly bright illuminating power of the LEDs
- 4, 6, 7, 11, 19, 32, 35 DMX channels selectable for various applications
- Each LED can be controlled individually
- Programmable color change speed, strobe effect and dimmer
- Strobe effect with 1-18 flashes per second
- RGBW color mixing
- Static colors
- Internal programs
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Manual, sound or DMX-controlled operation
- For large stage backgrounds in public places, main halls and lounges
- Hanging as well as standing installation possible
- Locking possibility at the mounting bracket
- Sound-controlled via built-in microphone
- Addressing via control panel with LCD screen
- Ready for connection with power-cable and plug
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

- DMX512 control possible via any commercial DMX controller
- Commandé via DMX

MADRIX NEO - Interface USB-DMX512

Interface USB/DMX Madrix pour un univers DMX, XLR

- MADRIX NEO is a reliable, easy-to-use, and high-quality DMX512 USB hardware interface including MADRIX software for LED control and MADRIX 3 software license
- The interface can be used for DMX input or DMX output to connect DMX512 devices to your computer
- The MADRIX software license for 512 DMX channels per device is already included and automatically activated when connected to MADRIX
- If you want to use DMX-IN, please use a 5-pin XLR male to 5-pin XLR male gender changer
- The MADRIX 3 Software license for 512 DMX channels per device is already included and automatically activated when connected to MADRIX
- Full USB 2.0 support, Power over USB, Hot Swapping, and Plug & Play
- Multiple devices can be used together without problems for larger projects
- Rugged metal housing with eye-catching design
- MADRIX is a powerful, easy-to-use, and award-winning LED lighting control software
- Allows you to realize all kinds of different LED projects and lighting designs
- A normal PC/laptop can be used for professional LED control
- Allows mapping in 2D (pixel mapping) as well as real, spatial 3D (voxel mapping)
- The software generates unique effects, visuals, and animations live and in real time
- No additional content is required
- Already includes a multitude of stock effects that are fully customizable (in speed, color, shape, direction, size, movement, position, brightness etc.)
- Analyzes incoming audio signals Sound2Light and Music2Light in real time
- New lighting scenes can easily be created in seconds
- Variety of options to combine visuals and graphical elements (layers, mix modes, filters, etc.)
- 256 x 256 Storage Places to organize and store effects
- DJ-like operation with 2 decks (Left/Right) and a crossfader
- 3 real-time previews to show your visual effects in advance (incl. 2D/3D, zoom, rotation)
- Controls up to 4 color channels per pixel/voxel (e.g. 1-channel, 2-channel, RGB, RGBW fixtures)
- Freely configurable Cue List for automated playback of a show (incl. time, date, duration, etc.)
- Supports Time Code from Art-Net, MIDI, SMPTE, and system time
- Remote control available via DMX-IN, Art-Net Remote, MIDI-IN, HTTP (internet browser), CITP
- Incl. Fixture Editor with large fixture library
- Includes various other tools and features (DMX Fader Tool, DMX Watcher, Matrix Generator, Patch Editor, Touch Screen window, backup system, scripting, mapping, scaling, etc.)
- MADRIX minimum system requirements: 2.0 GHz dual-core CPU, OpenGL 2.0 graphics card (NVIDIA recommended), 2 GB RAM, 1 GB free harddisk space, 1280 x 768 screen resolution, network card, sound card, USB 2.0
- Installation instructions and software available in English, Spanish, French, and Simplified Chinese
- User manuals also available at help.madrix.com
- More information available at www.madrix.com
- Peut recevoir et traiter jusqu'à 512 canaux DMX
- Peut envoyer jusqu'à 512 canaux DMX
- Commandé via DMX via USB
- Connexion enfichable NEUTRIK intégrée
- Made in Germany

Données techniques:

Poids:	13,04 kg

EUROLITE LED PIX-8 QCL Bar

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	180,00 W
Commande:	DMX
Fixtures disponibles pour:	Light´J; LED PC-Control 512
Dimension:	Longueur : 44,5 cm Profondeur : 13 cm Hauteur : 16,5 cm
Poids:	3,2 kg
Beam angle:	21°
LED number:	8
LED type:	8 W QCL
DMX channels:	4/6/7/11/19/32/35
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone
Dimensions (L x W x H):	445 x 130 x 165 mm

MADRIX NEO - Interface USB-DMX512

Alimentation électrique:	5V CC 500 mA
Branchement électrique:	Alimentation électrique via USB, type B câble d'alimentation pour raccordement au réseau USB A (inclus dans la livraison) Tramite
Canaux DMX:	Entrée 512 Sortie 512
Sortie DMX:	1 x XLR (F) 5 broches version encastrée
Commande:	DMX via USB
Port USB:	USB 2.0, type B
Utilisation de la marque:	Connexion enfichable NEUTRIK intégrée
Dimension:	Largeur : 7,8 cm Profondeur : 5,9 cm Hauteur : 3,5 cm
Poids:	0,24 kg

Contenu de la livraison:

1 x Appareil
1 x Mode d'emploi
1 x CD
1 x Câble USB

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.