

## OMNITRONIC CS-812 Powered Mixer

Universal powered stage mixer with DSP effects unit

Réf. : 10050150

GTIN: 4026397230802



L'article n'est plus disponible.

### Caractéristiques:

- Low-noise 8-channel mic/line mixer and amplifier with 2 x 350 W/4 ohms output power
- Integrated DSP effect unit with LED display 256 effects
- 8 mono input channels (XLR and 6.3 mm jack) with gain control, 3-band EQ, pan and effect control
- Insert or direct out (6.3 mm jack) per channel
- Aux send per channel for controlling external effectors
- Adjustable aux return input (6.3 mm jack)
- 2 adjustable CD inputs (stereo RCA) with crossfader
- Tape output (stereo RCA)
- +48V phantom power, can be switched centrally
- 2 x 7-band graphic equalizer for fine-tuned sound
- Precise 10-fold stereo LED meter
- 2 Speaker outputs

### Logistique

EAN / GTIN: 4026397230802

Poids: 17,25 kg

Longueur: 0.42 m

Largeur: 0.42 m

Hauteur: 0.64 m

### Données techniques:

Alimentation électrique: 115/230 V CA, 50/60 Hz

Puissance totale de raccordement: 1200,00 W

Puissance de sortie: Max. 700 W

Dimension: Largeur : 54 cm  
Profondeur : 33 cm  
Hauteur : 32 cm

|                         |                              |
|-------------------------|------------------------------|
| Poids:                  | 14,00 kg                     |
| Inputs:                 |                              |
| 8 mono                  | XLR or balanced 6.3 mm jacks |
| 8 inserts               | balanced 6.3 mm jacks        |
| 1 aux return            | balanced 6.3 mm jacks        |
| 2 CD                    | RCA                          |
| Outputs:                |                              |
| 2 master                | Speaker sockets              |
| 1 aux send              | balanced 6.3 mm jacks        |
| 8 insert                | balanced 6.3 mm jacks        |
| 1 Tape                  | RCA                          |
| Frequency range:        |                              |
| Microphone:             | 10-60000 Hz, ±3 dB           |
| Mono:                   | 10-60000 Hz, ±3 dB           |
| Stereo:                 | 10-55000 Hz, ±3 dB           |
| Distortion:             | 0.01 %                       |
| S/N-ratio:              | 112 dB                       |
| Tone control/channel:   |                              |
| Treble:                 | ±15 dB at 12 kHz             |
| Middle:                 | ±15 dB at 2.5 kHz            |
| Bass:                   | ±15 dB at 80 Hz              |
| Power output sine:      |                              |
| Stereo 4 ohms:          | 2 x 350 W                    |
| Dimensions (W x D x H): | 540 x 330 x 320 mm           |

## Contenu de la livraison: