

OMNITRONIC CL-266 Compressor/limiter

Gate/compresseur/limiteur/limiteur peak-stop à 2 canaux

Réf. : 10355590

GTIN: 4026397233278



L'article n'est plus disponible.

Description:

One device - many possibilities!

Just like mobile phones being a telephone, camera and organizer; our OMNITRONIC CL-266 combines various functions in one device. It is a compressor as well as a limiter, gate and peak. And that for very special reasons: to decrease blasting and to process, if appropriate, signals to guarantee a smooth flow of its chain. The CL-266 is adaptable from stereo- in two-channel mono operation and offers its numerous tuning possibilities, for example threshold-, ratio-, attack-, release- or level-compensator, separate for every channel. The very solid gadget, which is equipped with 1 unit, can be used technically as well as creatively for the intentional alteration of sounds.

Try it in your studio, home studio or in your club. You will be impressed with the result.

Logistique

EAN / GTIN: 4026397233278

Poids: 2,60 kg

Longueur: 0.55 m

Largeur: 0.20 m

Hauteur: 0.08 m

Caractéristiques:

- Dedicated 2-channel dynamic processor
- Switchable from stereo to 2-channel mono operation
- Independent gate, compressor/limiter, peak stop section per channel
- Variable gate with threshold and release control
- Threshold, ratio, attack, release, level control per channel
- Bypass switch allows instant comparison of original sound with processed sound
- Precise 7-digit LED meters for output level and gain reduction
- Inputs and outputs via balanced XLR connectors and 6.3 mm jacks
- Rack installation, 1 U

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	10,00 W
Dimension:	Largeur : 48,3 cm Profondeur : 14,7 cm Hauteur : 4,45 cm
Poids:	2 kg
Audio inputs/outputs:	XLR and 6.3 mm jack
Input impedance:	10/20 kohms (unb./bal.)
Output impedance:	300/150 kohms (unb./bal.)
Frequency range:	20-20000 Hz, ±3 dB
S/N ratio:	90 dB, unweighted
Crosstalk:	>80 dB
THD:	0.05%
Gate section	
Threshold:	variable (-45 to +10 dBu)
Release time:	variable (0.1 ms to 2 s)
Compressor section	
Threshold:	variable (-40 to +22 dBu)
Ratio:	variable (1:1 to 00:1)
Attack time:	variable (0.1 ms to 100 ms)
Release time:	variable (0.05 s to 2.5 s)
Output:	variable (-18 to +18 dB)
Peak stop section	
Level:	variable (-45 to +10 dBu)
Display	
Gain reduction:	VU meter, 7 LEDs
Output level:	VU meter, 7 LEDs
Dimensions (W x D x H):	483 x 147 x 46 mm

Contenu de la livraison: