

## OMNITRONIC DFE-212 Feedback exterminator

Feedback-free weekends guaranteed

Réf. : 10356510

GTIN: 4026397177787



### Caractéristiques:

- The feedback exterminator avoids quickly and effectively any occurring feedbacks in your amplifying system
- Connection via balanced XLR sockets or jacks
- 12 automatically controlled feedback frequencies per channel
- 3 different modes: Single, Auto, Manual
- MIDI-control possible

### Logistique

EAN / GTIN: 4026397177787

Poids: 2,85 kg

Longueur: 0.52 m

Largeur: 0.25 m

Hauteur: 0.09 m

### Données techniques:

|                                   |                                                                |
|-----------------------------------|----------------------------------------------------------------|
| Alimentation électrique:          | 115/230 V CA, 50/60 Hz                                         |
| Puissance totale de raccordement: | 10,00 W                                                        |
| Dimension:                        | Largeur : 48,3 cm<br>Profondeur : 15,2 cm<br>Hauteur : 4,45 cm |
| Poids:                            | 2,15 kg                                                        |
| Inputs:                           | XLR or balanced 6.3 mm jack                                    |
| Nominal Operating Level:          | -20 dB to +4 dB                                                |
| Max. input level:                 | +16 dB at +4 dB nominal level, +2 dB at -20 dB nominal level   |
| Input impedance:                  | 40 ohms balanced, 20 ohms unbalanced                           |

|                         |                                                              |
|-------------------------|--------------------------------------------------------------|
| Outputs:                | XLR or balanced 6.3 mm jack                                  |
| Max. output level:      | +16 dB at +4 dB nominal level, +2 dB at -20 dB nominal level |
| Output impedance:       | 66 ohms balanced, 33 ohms unbalanced                         |
| Frequency range:        | 20-20000 Hz                                                  |
| Distortion:             | 0.06 %                                                       |
| S/N-ratio:              | 98 dB, 20-20000 Hz                                           |
| Crosstalk:              | -95 dB, 20-20000 Hz                                          |
| MIDI-Interface:         | 5-pin DIN-socket IN/OUT/THRU                                 |
| Converters:             | 24-bit Sigma-Delta, 64/128-times oversampling                |
| Sampling rate:          | 48 kHz                                                       |
| Dimensions (W x D x H): | 482 x 152 x 45 mm                                            |

## Contenu de la livraison: