

OMNITRONIC E-1600 MK2 amplifier

Stereo PA amplifier with limiter

Réf. : 10451068

GTIN: 4026397537932



Caractéristiques:

- Class AB circuitry
- 3 operating modes can be selected (stereo, parallel bridged)
- Limiter, switchable
- Speaker switch-on delay
- 2 level controls
- Each channel with LED for activated protective circuit (protect) and 7-fold output meter with clip LED
- Complete protection set against short-circuit, overheat, DC voltage, power on/off transients
- Groundlift switch against humming
- Selectable input sensitivity
- Fan cooling
- Speaker outputs via lockable Speaker jacks and pairs of screw terminals
- Signal inputs via XLR or 6.3 mm mounting jacks
- Additional Speaker plug for 8-ohm bridge operation
- 8-ohm bridge operation via screw terminals or additional Speaker plug
- Rack installation
- (19") 48,3 cm installation en rack

Logistique

EAN / GTIN: 4026397537932

Poids: 15,85 kg

Longueur: 0.52 m

Largeur: 0.47 m

Hauteur: 0.18 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance de sortie:	550 W RMS (8 Ohm)
Conception du boîtier:	(19") 48,3 cm installation en rack

