

OMNITRONIC HDA-2.2 Amplifier

Amplificateur de puissance à 3 canaux 2 x 160 W + 350 W @ 4 ohms

Réf. : 10452350

GTIN: 4026397245493



L'article n'est plus disponible.

Description:

With up to 2,300 watts of built-in power, the HDA series is the perfect power source for various professional PA systems capable of high volume. Thanks to its three-channel design and the integrated frequency filters the series is optimized for stereo operation with satellite cabinets and a mono subwoofer. This series is ideally suited for bars and clubs, restaurants, dancing schools and gyms.

Caractéristiques:

- 2 x 100 W + 200 W @ 8 ohms
- 2 x 160 W + 350 W @ 4 ohms
- Low Cut switch on the rear panel
- Rotary control for adjusting the upper crossover frequency (Hi Cut) of the subwoofer
- 3 gain controls
- All operation modes controllable via LEDs, can be switched off
- Signal inputs via XLR female or terminal block
- Speaker connection via terminal block or speaker jacks
- Many protection circuits for optimized equipment protection
- Forced fan cooling
- Very rugged housing
- Rack installation

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Logistique

EAN / GTIN: 4026397245493

Poids: 21,50 kg

Longueur: 0.55 m

Largeur: 0.54 m

Hauteur: 0.14 m

Puissance de sortie:	Max. 670 W
Plage de fréquence:	20 - 20000 Hz
Dimension:	Largeur : 48,3 cm Profondeur : 45 cm Hauteur : 8,9 cm
Poids:	20 kg
Power output sine:	
Stereo 4 ohms	2 x 160 W + 350 W
Stereo 8 ohms	2 x 100 W + 200 W
Damping factor:	>250
Distortion factor:	0.05 %
Signal-to-Noise ratio:	>95 dB
Min. input sensitivity:	0.775 V RMS
Input impedance:	10 kohms (unbalanced), 20 kohms (balanced)
Output impedance:	>0.02 ohms
Slew rate:	20 V/μ sec
LED indicators (per channel):	Clip, Protect, Signal
Minimum mounting depth:	470 mm

Contenu de la livraison: