

## OMNITRONIC HDA-2.2 Amplifier

Amplificateur de puissance à 3 canaux 2 x 160 W + 350 W @ 4 ohms

Réf. : 10452350

GTIN: 4026397245493



### Description:

With up to 2,300 watts of built-in power, the HDA series is the perfect power source for various professional PA systems capable of high volume. Thanks to its three-channel design and the integrated frequency filters the series is optimized for stereo operation with satellite cabinets and a mono subwoofer. This series is ideally suited for bars and clubs, restaurants, dancing schools and gyms.

### Logistique

EAN / GTIN: 4026397245493

Poids: 21,50 kg

Longueur: 0.55 m

Largeur: 0.54 m

Hauteur: 0.14 m

### Caractéristiques:

- 2 x 100 W + 200 W @ 8 ohms
- 2 x 160 W + 350 W @ 4 ohms
- Low Cut switch on the rear panel
- Rotary control for adjusting the upper crossover frequency (Hi Cut) of the subwoofer
- 3 gain controls
- All operation modes controllable via LEDs, can be switched off
- Signal inputs via XLR female or terminal block
- Speaker connection via terminal block or speaker jacks
- Many protection circuits for optimized equipment protection
- Forced fan cooling
- Very rugged housing
- Rack installation

### Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

|                               |                                                             |
|-------------------------------|-------------------------------------------------------------|
| Puissance de sortie:          | Max. 670 W                                                  |
| Plage de fréquence:           | 20 - 20000 Hz                                               |
| Dimension:                    | Largeur : 48,3 cm<br>Profondeur : 45 cm<br>Hauteur : 8,9 cm |
| Poids:                        | 20 kg                                                       |
| Power output sine:            |                                                             |
| Stereo 4 ohms                 | 2 x 160 W + 350 W                                           |
| Stereo 8 ohms                 | 2 x 100 W + 200 W                                           |
| Damping factor:               | >250                                                        |
| Distortion factor:            | 0.05 %                                                      |
| Signal-to-Noise ratio:        | >95 dB                                                      |
| Min. input sensitivity:       | 0.775 V RMS                                                 |
| Input impedance:              | 10 kohms (unbalanced), 20 kohms (balanced)                  |
| Output impedance:             | >0.02 ohms                                                  |
| Slew rate:                    | 20 V/μ sec                                                  |
| LED indicators (per channel): | Clip, Protect, Signal                                       |
| Minimum mounting depth:       | 470 mm                                                      |

### Contenu de la livraison: