

## OMNITRONIC DD-4750 USB turntable

Direct drive DJ turntable with USB interface and recording software

Réf. : 10603020

GTIN: 4026397356076



### Caractéristiques:

- Direct drive high-torque motor
- Quartz-controlled for highest speed precision
- Built-in USB port and additional phono preamplifier, for a high-quality and convenient digitization of analog vinyl records
- Plug & play: no driver installation required, unit is identified automatically
- Sampling rates of 44.1 kHz and 48 kHz in stereo, resolution: 16 bits
- Incl. software for recording and editing
- 3 speeds (33 1/3, 45 and 78 RPM), pitch control  $\pm 10\%$ ,  $\pm 20\%$ ,  $\pm 50\%$
- Quick start
- 2 large start/pause buttons
- Selectable quartz-controlled pitch lock
- Motor with reverse run can be switched off
- Plug-in LED target lamp
- Adjustable anti-skating
- Tone arm height adjustable
- Shock-absorbing feet
- Switchable phono/line output
- Delivery includes pick-up system, slipmat, RCA and USB cable
- USB 1.1 support
- Suitable for Windows XP, Vista, 7 and Mac OS X
- Delivery without dust cover

### Logistique

EAN / GTIN: 4026397356076

Poids: 10,90 kg

Longueur: 0.52 m

Largeur: 0.43 m

Hauteur: 0.20 m

## Données techniques:

|                                   |                                                              |
|-----------------------------------|--------------------------------------------------------------|
| Alimentation électrique:          | 115/230 V CA, 50/60 Hz                                       |
| Puissance totale de raccordement: | 13,50 W                                                      |
| Plage de fréquence:               | 50 - 20000 Hz                                                |
| Dimension:                        | Largeur : 44,9 cm<br>Profondeur : 37 cm<br>Hauteur : 14,5 cm |
| Poids:                            | 9,80 kg                                                      |
| Type:                             | manual turntable                                             |
| Drive method:                     | quartz-controlled direct drive                               |
| Motor:                            | brushless DC motor                                           |
| Turntable platter:                | d=330 mm, aluminum diecast                                   |
| Speed:                            | 33 1/3 RPM, 45 RPM and 78 RPM                                |
| Change time between speeds:       | <0.3 sec                                                     |
| Initial torque:                   | >3.5 kg/cm                                                   |
| Start time:                       | <0.3 sec                                                     |
| Brake:                            | electronic brake                                             |
| Stop time:                        | <0.3 sec                                                     |
| Pitch adjustment:                 | ±10 %, ±20 %, ±50 %                                          |
| Wow and flutter:                  | <0.1 %                                                       |
| Rumble:                           | 55 dB DIN B                                                  |
| Tone arm:                         | S-shape with Cardan's suspension                             |
| Tone arm length:                  | 230 mm                                                       |
| Overhang:                         | 15 mm                                                        |
| Anti-skating range:               | 0-4 g                                                        |
| Applicable cartridge weight:      | 6-10 g                                                       |
| Stylus pressure range:            | 3-4 g                                                        |
| Phono output level:               | 1.5-3.6 mV/ 1 kHz 5 cm/sec                                   |
| Line output level:                | 90-216 mV/ 1 kHz 5 cm/sec                                    |
| Channel separation:               | >15 dB                                                       |
| Output connectors:                | RCA, USB type B                                              |
| Dimensions:                       | 449 x 370 x 145 mm                                           |

## Contenu de la livraison: