

## OMNITRONIC BD-1520 Turntable bk

Platine DJ à entraînement par courroie, noir

Réf. : 10603045

GTIN: 4026397066708



**L'article n'est plus disponible.**

### Caractéristiques:

- Delivery includes high-quality pick-up system qualified for back-cueing
- Adjustable  $\pm 10\%$  speed control
- Large start/stop button
- Instant start due to a powerful motor; short stop time via belt
- Remote start possible via 6.3 mm connection (1/4") on the rear panel
- Strobe lamp for exact speed adjustment
- Target lamp
- Delivery includes removable dustcover
- Adjustable anti-skating
- Shock-absorbing feet

### Logistique

EAN / GTIN: 4026397066708

Poids: 11,60 kg

Longueur: 0.54 m

Largeur: 0.43 m

Hauteur: 0.22 m

### Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 8,00 W

Dimension: Largeur : 45 cm  
Profondeur : 35,2 cm  
Hauteur : 14,8 cm

Poids: 10,35 kg

Type: Manual turntable

Drive method: Belt drive

|                                 |                                  |
|---------------------------------|----------------------------------|
| Motor:                          | DC motor                         |
| Speed:                          | 33 1/3 RPM and 45 RPM            |
| Change time between the speeds: |                                  |
|                                 | 33 ->45 RPM in <1 sec            |
|                                 | 45 ->33 RPM in <5 sec            |
| Pitch adjustment:               | ±10 %                            |
| Initial torque:                 | >650 g/cm                        |
| Wow and flutter:                | <0.25 %                          |
| Start time:                     | <1 sec                           |
| Stop time:                      | <1 sec                           |
| Rumble:                         | 50 dB DIN B                      |
| Platter:                        | Outer diameter 320 mm            |
| Tonearm:                        | S-shape with Cardan's suspension |
| Tonearm length:                 | 234 mm                           |
| Overhang:                       | 16 mm                            |
| Adjustable stylus pressure:     | 0-4 g                            |
| Anti-skating range:             | 0-7 g                            |
|                                 | 115 V/60 Hz                      |
| Maximum starting current:       | 260 mA                           |
| Output connectors:              | RCA, 6.3 mm jack                 |
| Dimensions:                     | 450 x 352 x 148 mm               |

## Contenu de la livraison: