

OMNITRONIC DD-2550 USB Turntable sil

Direct drive DJ turntable with switchable phono/line output and USB interface

Réf. : 10603061

GTIN: 4026397295016



Description:

Direct-driven record player with phono/line switch

Digitize your old vinyl treasures in a few steps with the direct-driven turntable Omnitronic DD-2520 USB.

Copying is a child's play

Thanks to the integrated USB interface and software you can record your favorite vinyls on your PC. You don't need any drivers, the player is identified automatically. A phono pre-amp is inbuilt and helps you to digitize your music without the need of additional hifi amps or DJ mixers.

Phono/line switch

You can also simply play and enjoy your records with the DD-2520. The switchable phono/line output enables you to connect the player to almost any sound system with phono or line input.

Fully-fledged DJ turntable

As the DD-2520 shows a precision drive, a rugged housing and shock-absorbing feet, it is perfectly suited to as player in your DJ set at home.

Logistique

EAN / GTIN: 4026397295016

Poids: 12,40 kg

Longueur: 0.53 m

Largeur: 0.41 m

Hauteur: 0.20 m

Caractéristiques:

- Built-in USB port and additional phono preamplifier, for a high-quality and convenient digitization of analog vinyl records
- Driver installation not required, unit is identified automatically
- Sampling rates of 44.1 kHz and 48 kHz in stereo, resolution: 16 bits
- Incl. software for recording and editing
- Precision direct drive

- Delivery includes pick-up system
- 2 speeds, pitch control $\pm 10\%$
- Large start/stop button
- Strobe lamp for exact speed adjustment
- Target lamp
- Delivery includes removable dustcover
- Adjustable anti-skating
- Shock-absorbing feet
- Switchable output phono/line
- USB 1.1 support
- Suitable for Windows XP, Vista, 7 and Mac OS X
- Réglage du niveau: $\pm 10\%$
- L'appareil peut être connecté au PC via USB,

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	12,00 W
Branchement électrique:	Fixe câble d'alimentation à prise euro Tramite
Plage de fréquence:	20 - 20000 Hz
Type d'entraînement:	Entraînement direct Moteur à courant continu sans balais
Transmission:	Couple de démarrage: 1 kg/cm Durée de démarrage: 1 sec. Durée de décélération: 1 sec. Transition de la vitesse de rotation: <1s 1kHz 5cm/sec
Pleurage et scintillement:	<0,15 % WRMS
Grondement:	55 dB DIN B
Vitesse de rotation:	33 tr/min; 45 tr/min
Bras de lecture:	En forme de S avec une suspension à cardan Longueur : 230 Surplomb : 16 mm Force d'appui : 0-4 g, réglable
Niveau de sortie:	Phono 1,5-3,6 mV/ 1 kHz 5 cm/sec Line 90-216 mV/ 1 kHz 5 cm/sec
Connexions:	Sortie: Line/Phono via RCA stéréo Sortie: USB B (F) version encastrable
Réglage du niveau:	$\pm 10\%$
Port USB:	USB 1.1, type B
Couleur:	Argenté
PC connect:	Via USB
Dimension:	Largeur : 45 cm Profondeur : 35 cm Hauteur : 15,5 cm
Poids:	11,30 kg
Dimension:	Diamètre : Ø 33 cm

Contenu de la livraison:

1 x Platine