

OMNITRONIC AS-800 Active system

Powerful compact active PA system, 800 W RMS

Réf. : 11038814

GTIN:



Caractéristiques:

- Mobile subwoofer/satellite system with class D circuitry
- Provides perfect sound and good level stability in various kinds of mobile PA applications up to medium-sized party events - ideal for solo entertainers, small bands and mobile discos
- Several active systems can be used to set up large PA systems
- 38 cm subwoofer in bassreflex cabinet provides powerful, dry bass
- Tops with 20 cm bass-midrange speakers and 8 cm titanium driver system
- Balanced inputs via combo jacks (XLR/6.3 mm) and XLR parallel outputs
- Microphone input (combo XLR/6.3 mm jack)
- Aux input (3.5 mm jack/RCA), ideal for portable music players (e.g. iPod)
- Adjustable volume balance between satellites
- Adjustable crossover frequency for subwoofer and satellites
- 5-band equalizer for fine-tuned sound of the master signal
- Stereo/mono selection
- Phase switchable for subwoofer
- Groundlift switch against humming
- MDF enclosure with scratch-resistant lacquer surface, impact-resistant steel grille and flange for speaker distance tube
- 4 castors, 2 of which with locking brakes
- Complete protection set against short-circuit, overheat, overload and overcurrent
- PowerCon input, power cable included
- Delivery includes two speaker cables

Logistique

Données techniques:

Puissance totale de raccordement:	900,00 W
Power supply:	230 V AC, 50 Hz
Power output sine:	
Subwoofer:	500 W RMS
Satellite speakers:	2 x 150 W RMS
Components:	
Subwoofer:	38 cm woofer (15")
Satellite speakers:	2 x 20 cm woofer (8"), 2 x 8 cm titanium tweeter (3.2")
Sensitivity:	
Subwoofer:	96 dB
Satellite speakers:	94 dB
Maximum SPL:	
Subwoofer:	123 dB
Satellite speakers:	114 dB
Frequency range:	
Subwoofer:	35-140 Hz
Satellite speakers:	140-20000 Hz
Inputs:	
Line:	combination XLR/6.3 mm jack L/R
Aux:	3.5 mm jack/stereo RCA
Mic:	combination XLR/6.3 mm jack
Outputs:	
Line:	XLR L/R (feed-through output)
Speaker:	2 x Speaker, 8 ohms
Protection circuits:	Short-circuit, overheat, overload, overcurrent
Dimensions (L x W x H):	
Subwoofer:	702 x 450 x 495 mm
Satellite speakers:	261 x 273 x 438 mm
Weight:	60 kg

Contenu de la livraison: