

OMNITRONIC LI-204W MK2 2-Way Top

Speaker with mount, 4" woofer, 1" dome tweeter, 30 W RMS

Réf. : 11038985

GTIN: 4026397493924



Caractéristiques:

- Dedicated full-range bassreflex system for fixed installation
- 10 cm (4") bass speaker and 25 mm (1") horn tweeter
- Attractive trapezoidal cabinet made of 8/12 mm plywood
- Scratch-resistant lacquer surface in black or white
- Supplied with movable mounting bracket for ceiling or wall installation
- Impact-resistant steel grille with acoustic foam
- 2 x M10 thread inserts
- For PA applications in restaurants, bars, discos and shops
- Avec étrier pivotant et inclinable pour une installation au mur ou au plafond, quel que soit l'angle

Logistique

EAN / GTIN: 4026397493924

Poids: 3,25 kg

Longueur: 0.17 m

Largeur: 0.15 m

Hauteur: 0.27 m

Données techniques:

Capacité de charge:	Programme: 60W Nominale: 30W RMS
Plage de fréquence:	100 - 20000 Hz
Sensibilité:	87 dB
Pression acoustique max.:	105 dB
Dispersion:	120° x 120°
Système d'enregistrement:	Étrier pivotant et inclinable pour une installation au mur ou au plafond, quel que soit l'angle
Connexions:	Enceinte via borne enfichable à vis

Fréquence de rupture:	3500 Hz
Enceinte:	1 x Boumeur 4" 1 x calottes aigus 1"
Type d'enceinte:	Enceinte en saillie (mur/plafond)
Couleur:	Blanc
Dimension:	Largeur : 15,2 cm Profondeur : 13,6 cm Hauteur : 24,5 cm
Poids:	3,10 kg

Contenu de la livraison: