

## OMNITRONIC PAS-212PRO-A 2-Way Top, active, DSP

Enceinte PA active 2 voies avec DSP

Réf. : 11039445

GTIN: 4026397531275



### Caractéristiques:

- Active 2-way speaker system for touring applications and permanent installations
- Class D circuitry with switch-mode power supply and 800 watts peak power
- DSP with 5 EQ presets and status display window
- Rugged full-range top speaker qualified for suspended installation and flange for stand installation
- Rotatable constant directivity horn (asymmetrical) with coil driver
- 30 cm woofer in bassreflex cabinet provides powerful, dry bass
- Power, signal and limiter indication
- Adjustable line input, (XLR/6.3 mm jack and RCA)
- Adjustable microphone input (XLR/6.3 mm jack), switchable to line
- Line output (XLR) for linking further active speaker systems
- Optimized for combination with PAS subwoofers
- Impact-resistant steel grille with acoustic foam
- Trapezoidal, multilayered glued plywood housing with monitor shape
- Can be used lying, standing, on a subwoofer, on a speaker stand or stand or suspended
- Suitable for car transport

### Logistique

EAN / GTIN: 4026397531275

Poids: 19,15 kg

Longueur: 0.45 m

Largeur: 0.42 m

Hauteur: 0.68 m

### Données techniques:

Alimentation électrique: 100-240 V CA, 50/60 Hz

Puissance totale de raccordement: 110 W

Capacité de charge: Programme: 800W  
Nominale: 400W RMS

|                         |                                                            |
|-------------------------|------------------------------------------------------------|
| Plage de fréquence:     | 55 - 20000 Hz                                              |
| Enceinte:               | 1 x Boumeur 12"                                            |
| Type d'enceinte:        | Boîtier compact                                            |
| Dimension:              | Largeur : 35,5 cm<br>Profondeur : 33 cm<br>Hauteur : 60 cm |
| Poids:                  | 17,20 kg                                                   |
| Components:             | 30 cm woofer (12"), 3.6 cm horn (1.4")                     |
| Input:                  |                                                            |
| Line:                   | Combination XLR/6.3 mm jack, RCA L/R                       |
| Mic:                    | Combination XLR/6.3 mm jack                                |
| Output:                 |                                                            |
| Line:                   | XLR                                                        |
| Sensitivity:            | 97 dB                                                      |
| Maximum SPL:            | 124 dB                                                     |
| Crossover frequency:    | 2 kHz                                                      |
| Dispersion angle:       | 50-100° x 55°                                              |
| Dimensions (H x W x D): | 600 x 355 x 330 mm                                         |

### Contenu de la livraison: