

OMNITRONIC PAS-215PRO 2-Way Top

Enceinte 2 voies pour applications de sonorisation

Réf. : 11039446

GTIN: 4026397438406



L'article n'est plus disponible.

Caractéristiques:

- PA speaker system for medium-sized and large discotheques
- Rugged full-range top speaker qualified for suspended installation
- Rotatable constant directivity horn (asymmetrical) with coil-driver
- Passive 2-way crossover, PTC tweeter protection
- Bass-reflex system for powerful, dry bass
- Balanced frequency range with high sound-pressure
- Very high durability
- Optimized for combination with PAS subwoofers
- Scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Flange for stand installation
- Trapezoidal wooden housing with monitor shape
- Can be used lying, standing, on a subwoofer, on a speaker stand or stand or suspended
- Suitable for car transport
- The combination of several PAS speakers allows for large PA systems

Logistique

EAN / GTIN: 4026397438406

Poids: 23,00 kg

Longueur: 0.52 m

Largeur: 0.45 m

Hauteur: 0.77 m

Données techniques:

Capacité de charge:	Programme: 800W Nominale: 400W RMS
---------------------	---------------------------------------

Plage de fréquence:	55 - 20000 Hz
---------------------	---------------

Impédance:	8 Ohm
------------	-------

Connexions:	Entrée: Enceinte via 2 x Boîtier d'enceinte encastrable (F)
Enceinte:	1 x Boumeur 15"
Type d'enceinte:	Boîtier compact
Dimension:	Largeur : 43 cm Profondeur : 36,5 cm Hauteur : 70 cm
Poids:	21,05 kg
Components:	38 cm woofer (15"), 2.5 cm horn (1")
Connection:	2 Speaker sockets
Sensitivity:	97 dB
Maximum SPL:	124 dB
Crossover frequency:	2 kHz
Dispersion angle:	50-100° x 55°

Contenu de la livraison: