

PSSO K-208 2-Way Top 200W

PRO PA speaker, 8" woofer, 1" horn, 200 W RMS, 8 ohms

Réf. : 11041098

GTIN: 4026397481815



Caractéristiques:

- Rugged full-range top speaker, qualified for suspension and touring applications
- Housing made of 15 mm birch plywood
- 20 cm (8") bass speaker with diecast aluminum basket
- Rotatable 25 mm constant directivity horn tweeter (1", 44 mm voice coil)
- Premium custom-made drivers by European manufacturer CELTO Acoustique
- Passive 2-way crossover
- Bassreflex system
- Parallel Neutrik Speakon connectors
- M10 thread for Omnimount wall brackets
- Adapter for stand installation available as accessory (SPA-10L)
- Trapezoidal multi-functional housing with scratch-resistant lacquer surface
- Impact-resistant steel grille with acoustic foam
- Applications: standing, as monitor, on a subwoofer or speaker stand, suspended
- Pilote de CELTO ACOUSTIQUE
- Connexion enfichable NEUTRIK intégrée
- Développé en europe

Logistique

EAN / GTIN: 4026397481815

Poids: 13,75 kg

Longueur: 0.34 m

Largeur: 0.34 m

Hauteur: 0.52 m

Données techniques:

Capacité de charge:	Programme: 400W Nominale: 200W RMS
---------------------	---------------------------------------

Plage de fréquence:	57 - 20000 Hz
---------------------	---------------

Sensibilité:	95 dB
--------------	-------

Pression acoustique max.:	124 dB
Dispersion:	90° x 60°
Impédance:	8 Ohm
Connexions:	Entrée: Enceinte via 2 x SpeakON 2 broches version encastrable (F)
Fréquence de rupture:	1800 Hz
Enceinte:	1 x Boumeur 8" 1 x Pavillon 1"
Type d'enceinte:	Boîtier compact
Utilisation de la marque:	Pilote de CELTO ACOUSTIQUE Connexion enfichable NEUTRIK intégrée
Dimension:	Largeur : 27 cm Profondeur : 27 cm Hauteur : 44,5 cm
Poids:	12,50 kg

Contenu de la livraison: