OMNITRONIC TMC-2 Interface incl. VDJ

DJ controller and interface incl. software Virtual DJ LE

Réf. : 11045042

GTIN: 4026397407570











Caractéristiques:

- USB controller with integrated audio interface for DJs - play, mix and scratch digital audio like vinyl records plus input and output options
- Optimized for control of the powerful audio and video mixing software Virtual DJ
- Supplied with Virtual DJ 6 Limited Edition, can be upgraded at discount price
- Supports all standard codecs, e.g. MP3, WAV, WMA, OGG, M4A, AAC, AVI, MPEG
- Integrated plug&play audio interface with high-resolution AD/DA converters (16 bits/48 kHz) for ultra-low latency operation under Windows XP/Vista/7 and Mac OS X
- Adjustable DJ microphone input (XLR and 6.3 mm jack) and line input (stereo RCA) for the master signal
- Master output (stereo XLR and stereo RCA) and booth output (stereo RCA) for PA applications with separate level controls and selectable source (PC signal or line input)
- Master output bass control
- Additional recording output (stereo RCA)
- Headphones output (3.5 mm and 6.3 mm jack) with level control for direct monitoring
- 2-channel mixer section:
- 3-band EQ, gain control and level fader per channel
- Ultra-smooth crossfader with adjustable curve
- Cue function with 3 hot cues
- Stereo LED level display
- Extra large track encoder for quick music library browsing
- Dual player section:
- Touch-sensitive jog dials with mode selector: pitch bend, scratch, fast search
- Dedicated sync function (auto beatmatching)
- Master Tempo (tonal pitch remains constant)
- Beat-accurate seamless loop
- Effect units with controls for selection and parameters

Logistique

EAN / GTIN: 4026397407570

Poids: 2,70 kg

Longueur: 0.41 m

Largeur: 0.31 m

Hauteur: 0.13 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

- Sample players with LED display, and controls for selection and level
- Powered via USB or included PSU
- Incl. USB cable
- Fully functional home version of the software available online under virtualdj.com
- Minimum system requirements PC: Windows XP(SP2)/Vista/7, Pentium IV , 1.6 GHz processor, 1 GB RAM
- Minimum system requirements Mac: OS X 10.4.11, Core Duo, 1.66 GHz processor, 1 GB RAM

Données techniques:

Dimension:	Largeur : 36 cm Profondeur : 26 cm Hauteur : 7 cm
Type:	USB controller
Power supply:	
	5 V DC, 500 mA via USB port or
	5 V DC, 1000 mA via supplied PSU
Inputs:	
DJ microphone:	3-pin XLR and 6.3 mm jack, bal.
Line:	stereo RCA
Outputs:	
Master:	3-pin stereo XLR and stereo RCA
Booth:	stereo RCA
Rec:	stereo RCA
Headphones output:	3.5 mm and 6.3 mm jack, bal.
USB port (type B):	2.0
Converter:	16 bits
Sample rate:	48 kHz
Dimensions:	360 x 260 x 70 mm
Weight:	1.7 kg

Contenu de la livraison:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.