

## OMNITRONIC TMC-3 Interface incl. VDJ

MIDI controller and audio interface incl. software Virtual DJ LE

Réf. : 11045044

GTIN: 4026397418729



### Caractéristiques:

- USB controller with integrated 4-channel sound card for DJs
- Play, mix and scratch digital audio like vinyl records
- 2 decks with selectable source: PC signal or line/phono
- Applicable for analog mixer operation without PC
- External output options for PA applications (XLR/RCA)
- Compatible to any MIDI controlled audio software, all MIDI controllers can be edited and freely assigned
- Optimized for control of the powerful audio and video mixing software Virtual DJ
- Supplied with Virtual DJ 7 Limited Edition, can be upgraded at discount price
- Integrated plug&play audio interface with high-resolution AD/DA converters (16 bits/48 kHz), applicable for Windows XP/Vista/7 and Mac OS X
- Supports all standard codecs, e.g. MP3, WAV, WMA, OGG, M4A, AAC, AVI, MPEG
- 2 line/phono inputs, switchable
- Adjustable DJ microphone input
- Master output and booth output with separate level controls
- Additional recording output
- Headphones output with level control for direct monitoring
- 2-channel mixer section:
- 3-band EQ, gain control and level fader per channel
- Ultra-smooth crossfader with adjustable curve
- Cue function with 3 hot cues
- Stereo LED level display
- Extra large track encoder for quick music library browsing
- Dual player section:
- Touch-sensitive jog dials with mode selector: pitch bend, scratch, fast search
- Dedicated sync function (auto beatmatching)

### Logistique

EAN / GTIN: 4026397418729

Poids: 2,70 kg

Longueur: 0.42 m

Largeur: 0.32 m

Hauteur: 0.12 m

- Master Tempo (tonal pitch remains constant)
- Beat-accurate seamless loop, can be edited
- Effect units with controls for selection and parameters
- Sample players with LED display, and controls for selection and level
- Powered via USB or included PSU
- Incl. USB cable
- Fully functional home version of the software available online under virtualdj.com
- Minimum system requirements PC: Windows XP(SP2)/Vista/7, Pentium IV , 1.6 GHz processor, 1 GB RAM
- Minimum system requirements Mac: OS X 10.4.11, Core Duo, 1.66 GHz processor, 1 GB RAM
- Samplingrate: 48 kHz

## Données techniques:

|                    |                                                                                                                                                                                           |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Samplingrate:      | 48 kHz                                                                                                                                                                                    |
| Connexions:        | Entrée: Line/Phono via 2 x RCA stéréo<br>Sortie: rec. via 1 x RCA stéréo<br>Sortie: Master via 1 x RCA stéréo<br>Sortie: Master via 2 x XLR 3 broches<br>Sortie: Booth via 1 x RCA stéréo |
| Port USB:          | USB 2.0, type B                                                                                                                                                                           |
| Convertisseur:     | 16 bit                                                                                                                                                                                    |
| Dimension:         | Largeur : 36 cm<br>Profondeur : 26 cm<br>Hauteur : 7 cm                                                                                                                                   |
| Poids:             | 2,20 kg                                                                                                                                                                                   |
| Type:              | USB MIDI controller                                                                                                                                                                       |
|                    | 5 V DC, 500 mA via USB port or                                                                                                                                                            |
|                    | 5 V DC, 1000 mA via supplied PSU                                                                                                                                                          |
| Inputs:            |                                                                                                                                                                                           |
| Line/phono:        | 2 x stereo RCA, switchable                                                                                                                                                                |
| DJ microphone:     | 3-pin XLR and 6.3 mm jack, bal.                                                                                                                                                           |
| Outputs:           |                                                                                                                                                                                           |
| Master:            | 3-pin stereo XLR and stereo RCA                                                                                                                                                           |
| Booth:             | stereo RCA                                                                                                                                                                                |
| Rec:               | stereo RCA                                                                                                                                                                                |
| Headphones output: | 3.5 mm and 6.3 mm jack, bal.                                                                                                                                                              |
| USB port:          | 2.0, type B                                                                                                                                                                               |
| Converter:         | 16 bits                                                                                                                                                                                   |
| Sample rate:       | 48 kHz                                                                                                                                                                                    |
| Dimensions:        | 360 x 260 x 70 mm                                                                                                                                                                         |

## Contenu de la livraison: