

INTUSONIC 4FW50T haut-parleur 4" large bande blanc

Haut-parleur d'installation 4" pour musique d'ambiance 20 W AES, 16 ohms

Réf. : 12604002

GTIN: 5060502923011



Description:

The INTUCAB 4FW50T is a wideband background music speaker for indoor applications where an unobtrusive appearance and mechanical ruggedness must be combined with above-average SPL and pristine sound quality. With 16 ohms of impedance, it is perfectly suited for low-impedance applications with up to 4 speakers in parallel, and the optionally available input transformer kit makes integration with 100V systems easy as well. Catering for the ease of cabling in fixed installations, an additional 5.0mm terminal strip is provided. The mounting options include M6 and M10 mounting points, allowing for suspended mounting, truss mounting and bracket mounting. Available in black and white structural paint finish for further flexibility. For full-range applications, a combination with the INTUCAB 8SM300T Subwoofer is recommended.

Logistique

EAN / GTIN: 5060502923011

Poids: 2,15 kg

Longueur: 0.21 m

Largeur: 0.20 m

Hauteur: 0.20 m

Caractéristiques:

- Option de kit de transformateur 100 V (UTK20 – vendu séparément)
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

Capacité de charge:	Nominale: 20W AES
	Programme: 40W
Plage de fréquence:	100 - 15000 Hz
Sensibilité:	84 dB (1 W/1 m)

Pression acoustique max.:	102,5 dB
Impédance:	16 Ohm
Système d'enregistrement:	Filetage M10 3x Filetage M6
Connexions:	2 x Boîtier d'enceinte encastrable (F) 1 x borne enfichable à vis
Enceinte:	Haut-parleur large bande 4"
Type d'enceinte:	Boîtier compact
Type de construction:	Enceinte fermée
Matériau:	MDF (panneaux de fibres à densité moyenne), 12 mm
Couleur:	Blanc, Surface structurée, verni
Dimension:	Largeur : 13 cm Profondeur : 16 cm Hauteur : 13,8 cm
Poids:	1,95 kg

Contenu de la livraison:

1 x tête d'ampli
 1 x Mode d'emploi
 1 x borne enfichable à vis
 3 x Œillet de fixation
 1 x adaptateur