

EUROLITE Distributeur de courant SBT-3216

Distributeur de courant 32 A pratique dans un boîtier 483 mm (19")

Réf. : 30248378

GTIN: 4026397521658



Caractéristiques:

- Specially designed for larger distribution needs
- 3 U necessary for installation
- 32 A three phase current input via power cable and plug
- The entire distributor is secured via two 30 mA Residual Current Devices (RCD)
- Control lamps indicate each phase
- 4 CEE sockets on the housing back (2 per RCD)
- Each CEE socket features fuse protection via 16 A automatic circuit breakers
- With M6 earthing screw in order to ground a rigg if necessary
- (19") 48,3 cm installation en rack 3 HE

Logistique

EAN / GTIN: 4026397521658

Poids: 6,90 kg

Longueur: 0.50 m

Largeur: 0.34 m

Hauteur: 0.22 m

Données techniques:

|                          |                                                                                                |
|--------------------------|------------------------------------------------------------------------------------------------|
| Alimentation électrique: | 380-400 V CA, 50 Hz                                                                            |
| Branchement électrique:  | Fixe câble d'alimentation et CEE 32 A 5 broches<br>Tramite                                     |
| Sortie de courant:       | 4 x CEE 16 A 5 broches (F) version encastrable<br>sécurisé                                     |
| Protection:              | 2 x disjoncteur différentiel (FI) 40A/0,03A 4-pol<br>4 x coupe-circuit automatique C 16A 3-pol |
| Conception du boîtier:   | (19") 48,3 cm installation en rack 3 HE                                                        |
| Dimension:               | Largeur : 48,3 cm<br>Profondeur : 24,5 cm                                                      |

Hauteur : 13,35 cm

Poids:

6,65 kg

**Contenu de la livraison:**