

EUROLITE Audience Blinder 2x50W LED COB 3200K

PRO audience blinder with 2 x 50 W COB LED

Réf. : 41606100

GTIN: 4026397458176



Caractéristiques:

- 3200 K color temperature
- 1, 2 or 4 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks and crossbeam systems
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Utilisable dans le mode CH DMX 2; 1

Logistique

EAN / GTIN: 4026397458176

Poids: 4,65 kg

Longueur: 0.46 m

Largeur: 0.20 m

Hauteur: 0.30 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	120 W
Fréquence du flash:	1 - 20 Hz
Canaux DMX:	2; 1
Fixtures disponibles pour:	Light´J; LED PC-Control 512; Light Captain

Angle de départ (1/2 pic):	60°
Température de couleur:	3200K
Dimension:	Largeur : 42 cm Profondeur : 24 cm Hauteur : 14 cm
Poids:	4,10 kg
DMX channels:	1/2/4
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
LED number:	2
LED type:	Array 50 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (L x W x H):	140 x 420 x 240 mm

Contenu de la livraison:
