

EUROLITE Audience Blinder 2x100W LED COB 3200K

Audience Blinder, distribution extensive 2 x 100 W-COB-LED (blanc chaud)

Réf. : 41606120

GTIN: 4026397455243



L'article n'est plus disponible.

Caractéristiques:

- 3200 K color temperature
- 1, 2 or 4 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks and crossbeam systems
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 device the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- 2 LED 100 W COB (Chip-on-board) blanc chaud (WW)
- Dimmer
- Effet stroboscope
- Utilisable dans le mode CH DMX 1; 2; 4
- Commandé via DMX
- Avec un Angle de départ de 60°

Logistique

EAN / GTIN: 4026397455243

Poids: 4,95 kg

Longueur: 0.47 m

Largeur: 0.20 m

Hauteur: 0.29 m

Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 260 W

Branchement électrique:	Alimentation électrique via PowerCON (bleu), version encastrable câble d'alimentation à prise contact de protection (inclus dans la livraison)
	Tramite
Sortie de courant:	1 x PowerCON (gris), version encastrable
Type de lampe:	Lampe LED
Type de LED:	2 x 100 W COB (Chip-on-board) blanc chaud (WW)
Fréquence du flash:	1 - 20 Hz
Équipement:	Dimmer
Canaux DMX:	1; 2; 4
Commande:	DMX
Fixtures disponibles pour:	Light´J; LED PC-Control 512; Light Captain
Angle de départ:	60°
Angle de départ (1/2 pic):	60°
Température de couleur:	3200K
Couleur du boîtier:	Noir
Dimension:	Largeur : 42 cm Profondeur : 14 cm Hauteur : 24 cm
Poids:	4,50 kg
DMX channels:	1/2/4
DMX connection:	5-pin and 3-pin XLR
Flash-rate:	20 Hz
LED number:	2
LED type:	Array 100 W, white
Color temperature:	3200 K
Beam angle:	60°
Dimensions (L x W x H):	140 x 420 x 240 mm

Contenu de la livraison:
