# EUROLITE Audience Blinder 4x50W LED COB 3200K

PRO audience blinder with 4 x 50 W COB LED

**Réf. : 41606125**

GTIN: 4026397467062











## L'article n'est plus disponible.

### Caractéristiques:

- 3200 K color temperature
- 1, 2, 4, 6 or 7 DMX channels selectable for various applications
- Each LED can be controlled individually
- Functions: built-in programs and strobe effect with variable speed, dimmer, Master/Slave
- Different dimmer curves and dimmer speed adjustable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- For use on stages, catwalks, crossbeam systems, or decoration
- Swivelable lamp rows
- Rugged housing and an appealing design
- Comfortable addressing and setting via control panel with LC display and four operating buttons
- Locking possibility at the mounting bracket
- Power connection via Neutrik PowerCon jack and included power cable
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- DMX control via every standard DMX controller
- Utilisable dans le mode CH DMX 2; 1

### Logistique

EAN / GTIN: 4026397467062
Poids: 11,00 kg
Longueur: 0.53 m
Largeur: 0.51 m
Hauteur: 0.26 m

### Données techniques:

| | |
|---|---|
| Alimentation électrique: | 230 V AC, 50 Hz |
| Puissance totale de raccordement: | 250 W |
| Fréquence du flash: | 1 - 20 Hz |
| Canaux DMX: | 2; 1 |

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

| | |
|---|---|
| Fixtures disponibles pour: | Light´J; Light Captain |
| Angle de départ (1/2 pic): | 60° |
| Température de couleur: | 3200K |
| Dimension: | Largeur : 40 cm<br>Profondeur : 49,5 cm<br>Hauteur : 17,5 cm |
| Poids: | 9,10 kg |
| DMX channels: | 1/2/4/6/7 |
| DMX connection: | 5-pin and 3-pin XLR |
| Flash-rate: | 20 Hz |
| LED number: | 4 |
| LED type: | Array 50 W, white |
| Color temperature: | 3200 K |
| Beam angle: | 60° |
| Dimensions (L x W x H): | 175 x 400 x 415 mm |

## Contenu de la livraison:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.