

EUROLITE LED ML-56 COB RGB 100 W Floor argent

Projecteur ML et LED COB 100 W mélange de couleurs RGB

Réf. : 41607321

GTIN: 4026397588279



Description:

ML spot with 100 W COB LED and RGB color mixing

The Eurolite LED ML-56 spotlight is equipped with a 100 Watts Chip-on-Board (COB) LED in RGB colors, which ensure homogeneous color mixing. It is suitable for use in theatres, on large stages as a front spotlight and for mobile use. Because of the additional stand bracket, the ML-56 can also be used as a floor spot.

The effect spotlight comes with a variety of functions: Automatic color change, internal and user-defined programs, dimmer and strobe effect with variably adjustable speed. The flicker-free projection even makes it possible to use the spotlight for video recording.

You can control the Eurolite LED ML-56 COB via DMX with master/slave function or in standalone mode. In addition, the built-in microphone allows you to operate the spotlight via music control. Comfortable addressing and setting is possible via the Control Board with four operating keys and LED display.

Logistique

EAN / GTIN: 4026397588279

Poids: 4,00 kg

Longueur: 0.29 m

Largeur: 0.29 m

Hauteur: 0.39 m

Caractéristiques:

- Equipped with one COB 100 W LED in RGB colors
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Adjustable white balance
- Dimmer speed (step response) adjustable
- Stand-alone, master/slave and DMX mode
- Color presets can be called up via DMX controller
- Strobe effect with adjustable speed
- 40° beam angle

- Control panel with LED display for easy configuration
- Additional bracket for floor use
- 2 swivel mounting brackets
- With color filter frame
- Optional barndoors available
- Ideal for theatres, large stages as pre-stage spot and mobile use
- Various versions available
- 1 LED 100 W COB (Chip-on-board) 3in1 RGB (mélange de couleurs homogène)
- Effet stroboscope
- Utilisable dans le mode CH DMX 3; 5; 6; 9
- L'appareil est refroidi par ventilateur
- Commandé via DMX; commande de la musique via microphone
- Exempt de scintillements
- Avec un Angle de départ de 40°

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	90 W
Classe de protection:	SK I
Branchement électrique:	Fixe câble d'alimentation à prise contact de protection Tramite
Longueur du câble:	Env. 1,2 m
Type de lampe:	Lampe LED
Type de LED:	1 x 100 W COB (Chip-on-board) 3in1 RGB (mélange de couleurs homogène)
Fréquence du flash:	0 - 17 Hz
Canaux DMX:	3; 3 (Teinte/saturation/niveau d'obscurité HSV); 5; 6; 9
Entrée DMX:	1 x XLR (M) 3 broches version encastrable
Sortie DMX:	1 x XLR (F) 3 broches version encastrable
Refroidissement:	Ventilateur
Commande:	DMX; commande de la musique via microphone
Fixtures disponibles pour:	EASY SHOW 1; Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Exempt de scintillements
Angle de départ:	40°
Angle de départ (1/2 pic):	40°
Angle de départ (1/10 pic):	82°
Couleur du boîtier:	Argenté
Dimension:	Largeur : 31 cm Profondeur : 26 cm Hauteur : 30 cm
Poids:	3,41 kg
Classification du bruit:	Classe 3 (bruits clairement perceptibles)

Contenu de la livraison:

1 x porte-filtre