

## EUROLITE AKKU UP-4 HCL Spot WDMX wh

LED Uplight with 4 x 12 W 6in1 LED & wireless DMX receiver (Wireless Solution)

Réf. : 41700561

GTIN: 4026397550863



**L'article n'est plus disponible.**

### Caractéristiques:

- Compact and bright
- Equipped with 4 x 12 W HCL LED in red, green, blue, amber, white and UV
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- With integrated folding foot for angled placement by floor installation
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 6, 8 or 12 DMX channels selectable
- Functions: static colors, stepless RGBAW+UV color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller
- Available in 2 housing colors: black and white
- 4 LED 12 W high-power 6in1 RGBWA/UV (mélange de couleurs homogène)
- Utilisable dans le mode CH DMX 6; 8; 12
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via DMX; stand-alone; W-DMX by Wireless Solution; commande de la musique via microphone
- Exempt de scintillements

### Logistique

EAN / GTIN: 4026397550863

Poids: 3,20 kg

Longueur: 0.23 m

Largeur: 0.20 m

Hauteur: 0.27 m

- Avec un Angle de départ de 22°
- **Appareil**
- Sans fil, flexible et polyvalent
- Durée de fonctionnement jusqu'à 8,5h en fonction du programme utilisé

## Données techniques:

|                                   |                                                                                                                                                                                                 |
|-----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Alimentation électrique:          | 100-240 V CA, 50/60 Hz                                                                                                                                                                          |
| Puissance totale de raccordement: | 37 W                                                                                                                                                                                            |
| Branchement électrique:           | Pile/batterie<br>Tramite<br>Alimentation électrique via appareils froids (M)<br>version encastrable câble d'alimentation à prise<br>contact de protection (inclus dans la livraison)<br>Tramite |
| Sortie de courant:                | 1 x appareils froids (F) version encastrable                                                                                                                                                    |
| Type de lampe:                    | Lampe LED                                                                                                                                                                                       |
| Type de LED:                      | 4 x 12 W high-power 6in1 RGBWA/UV (mélange<br>de couleurs homogène)                                                                                                                             |
| Canaux DMX:                       | 6; 8; 12                                                                                                                                                                                        |
| Entrée DMX:                       | 1 x XLR (M) 3 broches version encastrable                                                                                                                                                       |
| Sortie DMX:                       | 1 x XLR (F) 3 broches version encastrable                                                                                                                                                       |
| Refroidissement:                  | Refroidissement par convection passive                                                                                                                                                          |
| Commande:                         | DMX; stand-alone; W-DMX by Wireless Solution;<br>commande de la musique via microphone                                                                                                          |
| Fixtures disponibles pour:        | Light' J; LED PC-Control 512                                                                                                                                                                    |
| Projection:                       | Exempt de scintillements                                                                                                                                                                        |
| Fréquence porteuse:               | 2,4 GHz                                                                                                                                                                                         |
| Angle de départ:                  | 22°                                                                                                                                                                                             |
| Angle de départ (1/2 pic):        | 22°                                                                                                                                                                                             |
| Couleur du boîtier:               | Blanc                                                                                                                                                                                           |
| Dimension:                        | Largeur : 13,8 cm<br>Profondeur : 14,5 cm<br>Hauteur : 19,1 cm                                                                                                                                  |
| Poids:                            | 2,90 kg                                                                                                                                                                                         |
| Type de batterie:                 | 1 x Lithium-Ion 14,8 V, 6600 mAh, 97,68 Wh                                                                                                                                                      |
| Batterie:                         | Durée de fonctionnement jusqu'à 8,5h en fonction<br>du programme utilisé<br>Durée de charge 4,5h                                                                                                |
| Batterie:                         | 1 x pile bouton 3,0 V CR2025 lithium manganèse<br>intégré                                                                                                                                       |

## Contenu de la livraison:

- 1 x Appareil
- 1 x télécommande