

EUROLITE AKKU UP-4 HCL Spot WDMX wh

LED Uplight with 4 x 12 W 6in1 LED & wireless DMX receiver (Wireless Solution)

Réf. : 41700561

GTIN: 4026397550863



Caractéristiques:

- Compact and bright
- Equipped with 4 x 12 W HCL LED in red, green, blue, amber, white and UV
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- With integrated folding foot for angled placement by floor installation
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 6, 8 or 12 DMX channels selectable
- Functions: static colors, stepless RGBAW+UV color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller
- Available in 2 housing colors: black and white
- 4 LED 12 W high-power 6in1 RGBWA/UV (mélange de couleurs homogène)
- Utilisable dans le mode CH DMX 6; 8; 12
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via DMX; stand-alone; W-DMX by Wireless Solution; commande de la musique via microphone
- Exempt de scintillements

Logistique

EAN / GTIN: 4026397550863

Poids: 3,20 kg

Longueur: 0.23 m

Largeur: 0.20 m

Hauteur: 0.27 m

- Avec un Angle de départ de 22°
- Appareil**
- Sans fil, flexible et polyvalent
- Durée de fonctionnement jusqu'à 8,5h en fonction du programme utilisé

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	37 W
Branchement électrique:	Pile/batterie Tramite Alimentation électrique via appareils froids (M) version encastrable câble d'alimentation à prise contact de protection (inclus dans la livraison) Tramite
Sortie de courant:	1 x appareils froids (F) version encastrable
Type de lampe:	Lampe LED
Type de LED:	4 x 12 W high-power 6in1 RGBWA/UV (mélange de couleurs homogène)
Canaux DMX:	6; 8; 12
Entrée DMX:	1 x XLR (M) 3 broches version encastrable
Sortie DMX:	1 x XLR (F) 3 broches version encastrable
Refroidissement:	Refroidissement par convection passive
Commande:	DMX; stand-alone; W-DMX by Wireless Solution; commande de la musique via microphone
Fixtures disponibles pour:	Light' J; LED PC-Control 512
Projection:	Exempt de scintillements
Fréquence porteuse:	2,4 GHz
Angle de départ:	22°
Angle de départ (1/2 pic):	22°
Couleur du boîtier:	Blanc
Dimension:	Largeur : 13,8 cm Profondeur : 14,5 cm Hauteur : 19,1 cm
Poids:	2,90 kg
Type de batterie:	1 x Lithium-Ion 14,8 V, 6600 mAh, 97,68 Wh
Batterie:	Durée de fonctionnement jusqu'à 8,5h en fonction du programme utilisé Durée de charge 4,5h
Batterie:	1 x pile bouton 3,0 V CR2025 lithium manganèse intégré

Contenu de la livraison:

- 1 x Appareil
- 1 x télécommande