

ANTARI DarkFX Spot 1750

Spot UV DMX PRO, 4 x LED UV 16 W, longueur d'onde profonde (365 nm)

Réf. : 51100823

GTIN: 4719850658144



Description:

The Antari DarkFX Spot 1750 is an efficient high-output and low-power consumption UV LED spot that delivers a peak wavelength of 365 nm and radiant flux output of 19,080 mW at full intensity with minimum visible light. This ensures all UV-reactive materials reflect perfectly with stunningly bright and vivid colors.

Equipped with 4 x 16 W high-power UV LEDs, it features a 20° narrow beam angle, flicker-free operation, and special optics to prevent wear degradation from high UV exposure. This IP20-rated LED spot comes with an aluminium housing with an adjustable bracket for versatile mounting options.

The DarkFX Spot 1750 is operated in one of two modes: Either in DMX mode with 2 channels via the 5-pin XLR connectors or in stand-alone mode via the LCD display and the 4 operating buttons. Use the powerCON input to connect it to the mains.

Logistique

EAN / GTIN: 4719850658144

Poids: 3,85 kg

Longueur: 0.35 m

Largeur: 0.23 m

Hauteur: 0.25 m

Caractéristiques:

- Lumière visible minimale
- Haute performance à pleine intensité
- Optique spéciale conçue pour une forte exposition aux UV
- 4 LED 16 W high-power ultraviolet (UV)
- Effet UV
- Utilisable dans le mode CH DMX 2
- Commandé via stand-alone; DMX
- Avec un Angle de départ de 20°
- Connexion enfichable NEUTRIK intégrée

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	72 W
Branchement électrique:	Alimentation électrique via PowerCON (bleu), version encastrable câble d'alimentation à prise contact de protection (inclus dans la livraison) Tramite
Sortie de courant:	1 x PowerCON (gris), version encastrable
Type de lampe:	Lampe LED
Type de LED:	4 x 16 W high-power ultraviolet (UV)
Canaux DMX:	2
Entrée DMX:	1 x XLR (M) 5 broches version encastrée
Sortie DMX:	1 x XLR (F) 5 broches version encastrée
Commande:	Stand-alone; DMX
Angle de départ:	20°
Angle de départ (1/2 pic):	20°
Angle de départ (1/10 pic):	44°
Longueur d'onde:	365 nm
Couleur du boîtier:	Noir
Utilisation de la marque:	Connexion enfichable NEUTRIK intégrée
Poids:	3,26 kg

Contenu de la livraison:

- 1 x Appareil
- 1 x Mode d'emploi
- 1 x Câble secteur/câble d'alimentation
- 1 x Étrier
- 2 x vis moletée
- 4 x Cale