

EUROLITE FSM-150 Smoke machine

Fog machine with variable output angle

Réf. : 51701967

GTIN: 4026397336917



Description:

Fog clouds at its finest!

There is no doubt about the important role fog plays in the entertainment industry. But a fogger is not simply a fogger. Regarding the quality, great differences can be found. Presenting our EUROLITE FSM-150 we now offer you a professional unit, which is definitely no mistake, as it does convince through its outstanding workmanship, construction and power. In huge discotheques or on stages its preferences come into their own. It has a very strong smoke output up to 4 meters at its disposal. To prevent an unintentional after fogging. Moreover an automatic output stop was installed. A very useful characteristic: the variable output angle. With the FSM-150 it can be set approximately 70° upwards or downwards. Thus you can precisely control the fog and set it purposefully. Try it out. This reliable fogger will not leave you out in the rain!

Caractéristiques:

- Smoke machine with powerful smoke output
- Output angle adjustable by approx. 70° upwards and 70° downwards
- Control via supplied on/off remote control
- Remote control connection via 5-pin DIN socket
- Ideal for large discotheques or large stages
- With mounting bracket for hanging installation
- DMX control via every standard DMX controller
- Étendue de l'émission: Env. 4 m
- Grande capacité du réservoir
- Utilisable dans le mode CH DMX 1

Logistique

EAN / GTIN: 4026397336917

Poids: 13,80 kg

Longueur: 0.66 m

Largeur: 0.38 m

Hauteur: 0.33 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	1500 W
Temps de chauffe:	Env. 8 min
Volume de débit:	Env. 900 m³/min
Étendue de l'émission:	Env. 4 m
Capacité du réservoir:	5 l
Consommation de fluide:	Env. 50 ml/min
Canaux DMX:	1
Fixtures disponibles pour:	LED PC-Control 512
Dimension:	Largeur : 35 cm Profondeur : 56 cm Hauteur : 39 cm
Poids:	12,65 kg
DMX channels:	1
DMX connection:	3-pin XLR
Smoke-output:	4 m
Warm-up time:	8 min.
Fluid consumption:	50 ml/min.
Output volume:	900 m³/min.
Tank capacity:	5 l
Dimensions (L x W x H):	560 x 350 x 390 mm

Contenu de la livraison: