

LASERWORLD DS-1000RGB (ShowNET)

Diode laser à modulation de couleur analogique

Réf. : 51743250

GTIN: 7640144997304



Caractéristiques:

- Suitable for both beginners and professional users
- Multiple preset laser patterns included
- Control via DMX and ILDA
- Integrated Scan Fail Safety
- Low-maintenance due to Sealed Housing Technology
- P-Con terminals for power linking of several devices
- Interlock in and output
- Improved keylock
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via stand-alone; DMX; ILDA; Art-Net; commande de la musique via microphone

Logistique

EAN / GTIN: 7640144997304

Poids: 4,00 kg

Longueur: 0.31 m

Largeur: 0.29 m

Hauteur: 0.19 m

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	40 W
Branchement électrique:	Alimentation électrique via P-Con (bleu), version encastrable Tramite
Sortie de courant:	1 x P-Con (gris), version encastrable
Classe laser:	4
Couleur du laser:	R/G/B
Module laser:	Vert (G) 120 mW 520nm

	B bleu 700 mW 450 nm Rouge (R) 180 mW 638nm
Refroidissement:	Refroidissement par convection passive
Commande:	Stand-alone; DMX; ILDA; Art-Net; commande de la musique via microphone
Couleur du boîtier:	Noir
Dimension:	Largeur : 14 cm Profondeur : 20 cm Hauteur : 11 cm
Poids:	2,8 kg

Contenu de la livraison:

1 x Appareil
 1 x Mode d'emploi
 1 x Câble secteur/câble d'alimentation
 1 x Clé
 1 x clé Allen
 1 x Interlock