

FUTURELIGHT PRO Slim PAR-12 MK2 TCL

Projecteur LED PRO plat à 12 x LED 9 W 3in1 (RGB) sans ventilateur

Réf. : 51842562

GTIN: 4026397614015



L'article n'est plus disponible.

Description:

Flat, professional LED spot without fan

The FUTURELIGHT PRO Slim PAR-12 MK2 TCL is equipped with 12 powerful 3in1 tricolor LEDs in red, green and blue. The slim spot is suitable for use on larger stages and in discotheques. Thanks to the pure convection cooling, you can also use it in theatres or at galas, because it is noiseless in operation. Due to the compact and flat housing, you only need minimal space during installation.

The LEDs with RGB color mixing produce rich and homogeneous colors. The flicker-free Slim Spot is dimmable and has strobe settings with variable speed.

Several devices can be synchronised in master/slave mode. Powercon mains connections are located at the rear of the unit, allowing up to eight units to be operated in series. The LED spot can be controlled via DMX or in stand-alone mode.

Caractéristiques:

- Equipped with 12 x 3in1 tricolor LEDs in the colors red, green and blue
- Flat housing form requires minimal space when rigging
- Extremely compact housing in a beautiful design
- Second mounting bracket for safe standing installation
- Locking possibility at the brackets with large metal butterfly screws
- Functions: static colors, RGB color mixture, automatic color changes, dimmer, strobe effect with adjustable speed, Master/Slave operation
- Microphone-sensitivity adjustable via Control Board
- Addressing and setting via Control Board with four operating buttons and LED display
- Operable in stand-alone mode or via DMX

Logistique

EAN / GTIN: 4026397614015

Poids: 5,50 kg

Longueur: 0.25 m

Largeur: 0.25 m

Hauteur: 0.30 m

- Switch-mode power supply for operation between 100 and 240 volts
- P-Con terminals for power linking up to 8 units
- 12 LED 9 W high-power 3in1 RGB (mélange de couleurs homogène)
- Effet stroboscope
- Utilisable dans le mode CH DMX 3; 5; 7
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via stand-alone; DMX; commande de la musique via microphone
- Exempt de scintillements
- Avec un Angle de départ de 9°
- Fonctionnement silencieux

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	85 W
Branchement électrique:	Alimentation électrique via P-Con (bleu), version encastrable câble d'alimentation à prise contact de protection (inclus dans la livraison) Tramite
Sortie de courant:	1 x P-Con (gris), version encastrable
Type de lampe:	Lampe LED
Type de LED:	12 x 9 W high-power 3in1 RGB (mélange de couleurs homogène)
Canaux DMX:	3; 5; 7
Entrée DMX:	1 x XLR (M) 3 broches version encastrable
Sortie DMX:	1 x XLR (F) 3 broches version encastrable
Refroidissement:	Refroidissement par convection passive
Commande:	Stand-alone; DMX; commande de la musique via microphone
Fixtures disponibles pour:	Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Exempt de scintillements
Angle de départ:	9°
Angle de départ (1/2 pic):	9°
Angle de départ (1/10 pic):	20°
Couleur du boîtier:	Noir
Dimension:	Largeur : 28,7 cm Profondeur : 12,6 cm Hauteur : 30 cm
Poids:	5,00 kg
Classification du bruit:	Classe 0 (pas du tout de bruit)

Contenu de la livraison:

- 1 x Projecteur
- 1 x Mode d'emploi
- 1 x Câble secteur/câble d'alimentation