EUROLITE LED FLD-432 RGB 10mm Flood

High performance LED RGB floodlight

Réf. : 51913851

GTIN: 4026397297317











Description:

Bright as lightning!
All wine are not created equal, just as all lights are not created equal as well. The former is distinguished between vintage, finish or bouquet. Concerning light, characteristics like color, warmth and brightness are to the fore. Seeing the performance of our EUROLITE Flood Light and its 432 LEDs, you will understand, that lights can be differenced from one another quite clearly. Our flood light for example, can surpass its competitors in the field of brightness and enlightens a DJ's backplane on stage with great colors. This device provides the facility ether to enlighten all of its eight segments separately and in different colors or to let them shine in the same color at the same time. Furthermore, this product can easily replace an conventional spot like a PAR 56 and by doing so, saves energy due to its low power consumption. Ain't that bad.

Caractéristiques:

- Equipped with 432 x 10 mm LED (red: 18 x 8, green: 18 x 8, blue: 18 x 8)
- Manual, sound or DMX-controlled operation
- Functions: static colors; automatic color change, 14 built-in programs and strobe effect with variable speed; Master/Slave
- On-bord control bord with 2 x 8 character LC-display
- DMX512 control possible via any commercial DMX controller
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free
- Locking possibility at the mounting bracket
- Ready for connection with power cord and safety power plug
- Utilisable dans le mode CH DMX 26
- Commandé via commande de la musique via microphone

Logistique

EAN / GTIN: 4026397297317
Poids: 5,30 kg
Longueur: 0.62 m
Largeur: 0.26 m
Hauteur: 0.19 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	60 W
Canaux DMX:	26
Commande:	Commande de la musique via microphone
Angle de départ (1/2 pic):	30°
Dimension:	Largeur : 54 cm Profondeur : 19 cm Hauteur : 13,4 cm
Poids:	4,75 kg
Light ouput intensity:	R 30000 mcd
	G 30000 mcd
	B 20000 mcd
Beam angle:	20°
DMX channels:	Max. 26
LED number:	432 (10 mm)
Dimensions (L x W x H):	540 x 190 x 134 mm

Contenu de la livraison:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.