

## EUROLITE LED PAR-64 RGB 36x1W Short sil

PRO LED spotlight as DMX model

Réf. : 51914005

GTIN: 4026397392517



### Caractéristiques:

- Operable in stand-alone mode or via DMX interface
- DMX512 control possible via any commercial DMX controller (occupies 5 channels)
- 3 or 5 DMX channels selectable for numerous applications
- Sound-control via built-in microphone
- Adjustable microphone sensitivity via rotary control
- Comfortable addressing and setting via control panel with LED display and three operating buttons
- Functions: static colors, RGB color blend, 6 internal programs, dimmer and strobe settings via DMX, Master/Slave
- Equipped with 36 x 1 W LEDs
- Beam angle approximately 22°
- Locking possibility at the mounting bracket
- Ready for connection with power cord and safety plug
- Available as hanging spot or as floor spot
- Advantages of high-power LED technology: extreme light output, long life, low power consumption, defacto maintenance free with brilliant light radiation
- Utilisable dans le mode CH DMX 3

### Logistique

EAN / GTIN: 4026397392517

Poids: 2,64 kg

Longueur: 0.24 m

Largeur: 0.24 m

Hauteur: 0.35 m

### Données techniques:

Alimentation électrique: 230 V AC, 50 Hz

Puissance totale de raccordement: 90,00 W

Canaux DMX: 3

|                         |                                                            |
|-------------------------|------------------------------------------------------------|
| Dimension:              | Largeur : 29 cm<br>Profondeur : 30,5 cm<br>Hauteur : 37 cm |
| Poids:                  | 2,19 kg                                                    |
| DMX channels:           | max. 5                                                     |
| DMX connection:         | 3-pin XLR                                                  |
| Sound-control:          | via built-in microphone                                    |
| LED type:               | 1 W                                                        |
| LED number:             | 36                                                         |
| Beam angle:             | 22°                                                        |
| Dimensions (L x W x H): | 290 x 305 x 370 mm                                         |

**Contenu de la livraison:**