

EUROLITE LED PAR-64 QCL 12 x 8 W Floor argent

Projecteur PAR et 12 x 8-W-4in1-LED et mélange de couleurs RGBW

Réf. : 51914031

GTIN: 4026397613841



Description:

PAR spotlight with RGBW color mixing incl. remote control

The Eurolite LED PAR-64 is equipped with 12 powerful RGBW-LEDs (4in1) of 8 Watt each. You can use it on stage, in the club lighting area or as a floor spot, thanks to its additional bracket for placement.

The color temperature of the white tone is adjustable in six steps, the RGBW color mixing is stepless. 24 colors can be selected directly. The spotlight has a dimmer and strobe effect.

The effect spot can be controlled via DMX, standalone or via music control via the built-in microphone with adjustable microphone sensitivity. In auto and music mode you can play the integrated show programs.

Addressing and settings are possible via a control unit with four-digit LED display. Up to eight devices can be easily interconnected using the existing IEC mains connections.

The Eurolite LED PAR-64 can be easily remote controlled with the supplied infrared remote control.

Caractéristiques:

- 12 high-power 8 W RGBW LEDs (4in1)
- Built-in auto and music show programs
- Color temperature adjustable in 6 steps (2700-8000 K)
- Direct color selection for 24 preset colors
- Stepless RGBW color blend, color change, color fade, dimmer and strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Convenient wireless control via included IR remote control EUROLITE IR-7
- Swivel mounting bracket

Logistique

EAN / GTIN: 4026397613841

Poids: 3,00 kg

Longueur: 0.26 m

Largeur: 0.26 m

Hauteur: 0.34 m

- Additional bracket for floor use
- Feed-through output allows to power up to 8 devices
- Switch-mode power supply for operation between 100 and 240 volts
- 12 LED 8 W high-power 4in1 RGBW (mélange de couleurs homogène)
- Effet stroboscope
- Utilisable dans le mode CH DMX 2; 3; 4; 5; 6; 9
- Commandé via stand-alone; DMX; Télécommande infrarouge; commande de la musique via microphone; fonction maître/esclave
- Exempt de scintillements
- Avec un Angle de départ de 14°

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	70 W
Classe de protection:	SK I
Branchement électrique:	Alimentation électrique via appareils froids (M) version encastrable câble d'alimentation à prise contact de protection (inclus dans la livraison) Tramite
Sortie de courant:	1 x appareils froids (F) version encastrable
Type de lampe:	Lampe LED
Type de LED:	12 x 8 W high-power 4in1 RGBW (mélange de couleurs homogène)
Canaux DMX:	2; 3; 4; 5; 6; 9
Entrée DMX:	1 x XLR (M) 3 broches version encastrable
Sortie DMX:	1 x XLR (F) 3 broches version encastrable
Commande:	Stand-alone; DMX; Télécommande infrarouge; commande de la musique via microphone; fonction maître/esclave
Fixtures disponibles pour:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Projection:	Exempt de scintillements
Angle de départ:	14°
Angle de départ (1/2 pic):	14°
Angle de départ (1/10 pic):	29°
Couleur du boîtier:	Argenté
Dimension:	Largeur : 29,6 cm Profondeur : 27,3 cm Hauteur : 34 cm
Poids:	2,60 kg
Batterie:	1 x pile bouton 3,0 V CR2025 lithium manganèse intégré

Contenu de la livraison:

1 x télécommande