

EUROLITE LED IP CCR-1200 QCL Wall Light incl. Flight Case

PRO outdoor spotlight (IP65) in case with 120 x 8 W 4in1 LED (RGBW)

Réf. : 51914134

GTIN: 4026397573152



L'article n'est plus disponible.

Caractéristiques:

- DMX-controlled operation or stand-alone operation with Master/Slave function
- DMX control via any standard DMX controller
- 4, 7, or 11 DMX channels selectable
- With integrated wireless receiver for WDMX operation (Wireless Solution - made in Sweden)
- For architectural lighting
- Suitable for external use (IP65)
- For permanent installation
- Equipped with 120 x 4in1 QCL LED in the colors red, green, blue and white
- Stepless RGBW color blend
- Color macros
- Dimmer
- Dimmer speed (step response) adjustable
- Strobe effect with adjustable speed
- Internal programs
- Programmable color change speed
- Addressing and setting via Control Board with LED display and four operating buttons
- Switch-mode power supply for operation between 100 and 240 volts
- Feed-through output allows to power up to 8 devices
- Ready for connection via power cord with 3-pin 16A CEE plug
- Flightcase included in delivery
- 120 LED 8 W high-power 4in1 RGBW (mélange de couleurs homogène)
- Utilisable dans le mode CH DMX 4; 7; 11
- L'appareil est refroidi par ventilateur
- Commandé via stand-alone; DMX; W-DMX by Wireless Solution
- Exempt de scintillements
- Avec un Angle de départ de 15°

Logistique

EAN / GTIN: 4026397573152

Poids: 55,00 kg

Longueur: 0.72 m

Largeur: 0.50 m

Hauteur: 0.80 m

Article encombrant

- Convient à une utilisation en extérieur IP65

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	460 W
Type de protection:	IP65
Branchement électrique:	Fixe câble d'alimentation à prise contact de protection Tramite
Type de lampe:	Lampe LED
Type de LED:	120 x 8 W high-power 4in1 RGBW (mélange de couleurs homogène)
Fréquence du flash:	0 - 18 Hz
Canaux DMX:	4; 7; 11
Entrée DMX:	1 x XLR (M) 3 broches version encastrable
Sortie DMX:	1 x XLR (F) 3 broches version encastrable
Refroidissement:	Ventilateur
Commande:	Stand-alone; DMX; W-DMX by Wireless Solution
Fixtures disponibles pour:	Light´J; LED PC-Control 512
Projection:	Exempt de scintillements
Angle de départ:	15°
Angle de départ (1/2 pic):	15°
Angle de départ (1/10 pic):	48°
Couleur du boîtier:	Noir
Dimension:	Largeur : 65 cm Profondeur : 58 cm Hauteur : 67 cm
Poids:	54,90 kg

Contenu de la livraison: