

EUROLITE LED IP PAD 9x8W QCL

Weather-proof DMX spot (IP65) with 9 x 8 W 4in1 LED (RGBW)

Réf. : 51914158

GTIN: 4026397483024



Caractéristiques:

- 4, 6 or 7 DMX channels selectable for numerous applications
- Equipped with 9 x 8 W 4in1 LED in the colors red, green, blue and white
- For architectural lighting
- Suitable for external use (IP65)
- Compact, matt grey housing
- Functions: Static colors, RGBW color mixture, built-in programs, dimmer, strobe effect, Master/Slave operation
- Programmable color change speed and strobe effect
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Comfortable addressing and setting via Control Board with LC display and four operating buttons
- Infrared remote control in credit card format included in delivery
- Switch-mode power supply, automatic power supply adaption between 100 and 240 volts
- Feed-through output allows to power another device
- After every 8 devices the fixtures must have a renewed connection with the power mains
- 9 LED 8 W high-power 4in1 RGBW (mélange de couleurs homogène)
- Utilisable dans le mode CH DMX 4; 6; 7
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via stand-alone; DMX; Télécommande infrarouge
- Avec un Angle de départ de 15°
- Convient à une utilisation en extérieur IP65

Logistique

EAN / GTIN: 4026397483024

Poids: 4,75 kg

Longueur: 0.30 m

Largeur: 0.20 m

Hauteur: 0.31 m

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	65 W
Type de protection:	IP65
Branchement électrique:	Alimentation électrique via connecteur fileté (M) IP 3 broches câble d'alimentation à prise contact de protection (inclus dans la livraison) Tramite
Sortie de courant:	1 x connecteur fileté (F) IP 3 broches
Type de lampe:	Lampe LED
Type de LED:	9 x 8 W high-power 4in1 RGBW (mélange de couleurs homogène)
Canaux DMX:	4; 6; 7
Entrée DMX:	1 x connecteur fileté (M) IP 3 broches
Sortie DMX:	1 x connecteur fileté (F) IP 3 broches
Refroidissement:	Refroidissement par convection passive
Commande:	Stand-alone; DMX; Télécommande infrarouge
Fixtures disponibles pour:	Light´J; LED PC-Control 512
Angle de départ:	15°
Angle de départ (1/2 pic):	15°
Couleur du boîtier:	Gris
Dimension:	Largeur : 20,5 cm Profondeur : 12 cm Hauteur : 22,3 cm
Poids:	4,25 kg
Batterie:	1 x pile bouton 3,0 V CR2025 lithium manganèse intégré

Contenu de la livraison:

1 x télécommande