

EUROLITE LED IP PAR 36x1W RGB

Weather-proof DMX spotlight (IP65) with 36 x 1 W LED in red, green and blue

Réf. : 51914174

GTIN: 4026397434842



Caractéristiques:

- Equipped with 36 x 1 W LED: 12 x red, 12 x green and 12 x blue
- 3 or 5 DMX channels selectable for numerous applications
- Beam angle approximately 15°
- Locking possibility at the mounting bracket
- Ideal as floor spot via additional bracket
- Stepless RGB color change
- 7 color presets and 4 built-in programs
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Dimmer and strobe settings via DMX
- Suitable for external use (IP65)
- Perfect for architectural lighting in public places and buildings
- Addressing via control panel with 4-digit LED display
- Control via control panel with display or any regular DMX controller
- Feed-through output allows to power another device
- After every 8 spot the fixtures must have a renewed connection with the power mains
- 36 LED 1 W high-power R/G/B (mélange de couleurs homogène)
- Effet stroboscope
- Utilisable dans le mode CH DMX 3; 5
- L'appareil est refroidi par refroidissement par convection passive
- Commandé via stand-alone; DMX
- Avec un Angle de départ de 15°

Logistique

EAN / GTIN: 4026397434842

Poids: 4,30 kg

Longueur: 0.27 m

Largeur: 0.27 m

Hauteur: 0.32 m

Données techniques:

Alimentation électrique:	230 V AC, 50 Hz
Puissance totale de raccordement:	50 W
Type de protection:	IP65
Branchement électrique:	Alimentation électrique via connecteur fileté (M) IP 3 broches câble d'alimentation à prise contact de protection (inclus dans la livraison) Tramite
Sortie de courant:	1 x connecteur fileté (F) IP 3 broches
Type de lampe:	Lampe LED
Type de LED:	36 x 1 W high-power R/G/B (mélange de couleurs homogène)
Canaux DMX:	3; 5
Entrée DMX:	1 x connecteur fileté (M) IP 3 broches
Sortie DMX:	1 x connecteur fileté (F) IP 3 broches
Refroidissement:	Refroidissement par convection passive
Commande:	Stand-alone; DMX
Fixtures disponibles pour:	Light´J; LED PC-Control 512
Angle de départ:	15°
Angle de départ (1/2 pic):	15°
Couleur du boîtier:	Noir
Dimension:	Largeur : 24 cm Profondeur : 20 cm Hauteur : 32 cm
Poids:	3,85 kg

Contenu de la livraison:

1 x câble adaptateur