

EUROLITE LED BAR-650 RGB+UV 4in1

Barre LED (60cm), 6 x LED 4in1 RGB/UV, 5 W

Réf. : 51930433

GTIN: 4026397572261



L'article n'est plus disponible.

Caractéristiques:

- Equipped with six QCL LEDs in the colors red, green, blue and UV
- 1, 3, 4, 6, 7 or 12 DMX channels selectable
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Addressing and setting via Control Board with LED display and four operating buttons
- Additional controlling possibility via the EUROLITE IR-8 remote control, included in delivery
- Functions: Static colors, RGBUV color blend, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Every LED group (each with 2 LEDs) can be controlled individually in 12CH mode
- Sound-control via built-in microphone
- Hanging as well as standing installation possible
- Locking possibility at the brackets
- Switch-mode power supply for operation between 100 and 240 volts
- DMX control via every standard DMX controller
- Feed-through output allows to power up to 8 devices
- Ready for connection via enclosed IEC power cord with safety-plug
- 6 LED 5 W high-power 4in1 RGB/UV (mélange de couleurs homogène)
- Effet stroboscope
- Utilisable dans le mode CH DMX 1; 3; 4; 6; 7; 12
- Commandé via stand-alone; DMX; Télécommande infrarouge
- Exempt de scintillements
- Avec un Angle de départ de 20°

Logistique

EAN / GTIN: 4026397572261

Poids: 2,16 kg

Longueur: 0.58 m

Largeur: 0.12 m

Hauteur: 0.13 m

Données techniques:

Alimentation électrique:	100-240 V CA, 50/60 Hz
Puissance totale de raccordement:	30 W
Branchement électrique:	Alimentation électrique via appareils froids (M) version encastrable câble d'alimentation à prise contact de protection (inclus dans la livraison) Tramite
Sortie de courant:	1 x appareils froids (F) version encastrable
Type de lampe:	Lampe LED
Type de LED:	6 x 5 W high-power 4in1 RGB/UV (mélange de couleurs homogène)
Canaux DMX:	1; 3; 4; 6; 7; 12
Commande:	Stand-alone; DMX; Télécommande infrarouge
Fixtures disponibles pour:	Light´J; LED PC-Control 512
Projection:	Exempt de scintillements
Angle de départ:	20°
Angle de départ (1/2 pic):	20°
Angle de départ (1/10 pic):	38°
Couleur du boîtier:	Noir
Dimension:	Longueur : 60 cm Profondeur : 8 cm Hauteur : 8,5 cm
Poids:	1,93 kg
Batterie:	1 x pile bouton 3,0 V CR2025 lithium manganèse intégré
DMX connection:	3-pin XLR
Sound-control:	via built-in microphone

Contenu de la livraison:

1 x télécommande