SHZ Roundsling with Steel Inlay 3m/4000KG

Élingue ronde à insert en acier

Réf. : 58010755

GTIN: 4026397466584









Caractéristiques:

- Steelflex with window complies with BGV C1
- For attaching loads
- Made from polyester, complies with DIN EN 1492-2
- Single-coated, thermically fix
- Printed load capacity
- No danger of injury for the hands
- Smooth transport of goods
- Highly flexible
- UV resistant
- Correspond EN 1492-2
- La longueur utile est de 3 m

Logistique

EAN / GTIN: 4026397466584
Poids: 5,25 kg
Longueur: 0.39 m
Largeur: 0.39 m
Hauteur: 0.07 m

Données techniques:

Charge max. WLL (7 fois):	4000 kg
Norme:	EN 1492-2,
Couleur:	Noir
Plage de température:	-40° C - +100° C
Longueur utile:	3 m
Poids:	5,25 kg

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

Contenu de la livraison:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.