

ALUTRUSS Traverse 2 points DECOLOCK DQ2-4000

Système de traverse 2 points universel de conception légère

Réf. : 60301524

GTIN: 4026397497557



Prix de catalogue: 213.01 €

TVA 19% incl.

Description:

DECOLOCK DQ2 2-point truss system

DECOLOCK DQ2 is a 2-point truss system made of aluminum. The individual elements are connected via two cones, pivots and pins.

The advantage of the conical connection system is that the cones completely fit into the main chords so that highest load capacity is guaranteed. The Quick-Lock system enables fast, efficient and highly aesthetic assembly when the truss constructions are frequently assembled and dismantled.

The two main chords are made of 35 mm aluminum tube with 2 mm wall thickness and offer sufficient strength at a low weight. The braces have a diameter of 10 mm with 2 mm wall thickness and provide the system with a decorative appearance.

With DECOLOCK, you can realize compact installations with low self weight, e. g. for shop displays, shop decorations, exhibitions, interior design, fair booths, discotheques and theatres.

DECOLOCK is primarily designed for decorative installations and can be used for permanent or temporary installations due to its highly aesthetic appearance. The advantages of this system are the compact construction with 220 mm outer dimensions, low weight, optimum strength along with easy and quick assembly.

The documentation of this truss system is closely related to the Codes of Practice SQ P1 - Truss Systems published by the VPLT/PLASA. The load table as calculation base can be downloaded from the Internet before buying the product!

Logistique

EAN / GTIN: 4026397497557

Poids: 6,10 kg

Longueur: 4.02 m

Largeur: 0.23 m

Hauteur: 0.03 m

Article encombrant

Caractéristiques:

- Alliage d'aluminium pour un look classique et high-tech
- Montage rapide, efficace et fiable grâce aux connecteurs coniques QUICK-LOCK
- Un vaste choix de longueurs, d'éléments circulaires et d'angles offre un maximum de flexibilité
- Constructions spéciales selon les spécifications du client sur demande
- Tube porteur: 35 mm
- Chaque couleur RAL disponible sur demande
- Made in Europe
- Pour des domaines d'application tels que: Agencement de magasin; agencement de salons; centres sportifs/centres de fitness; scène; clubs/écoles de danse; bailleur; Agencement de salons et magasin
- Vous trouverez de plus amples informations sur ce produit dans la rubrique « Téléchargements » de la fiche technique

Données techniques:

Tube porteur:	35 mm x 2 mm
Procédé de soudure:	Impulsion WIG
Matière de soudure:	AlMg 5
Couleur:	Couleurs alu; chaque couleur RAL disponible sur demande
Entretoise diamètre x épaisseur:	10 x 2 mm
Dimension:	Longueur : 400 cm Largeur : 22 cm Hauteur : 3,50 cm
Poids:	5,20 kg

Contenu de la livraison:

- 1 x traverse
- 1 x set de connecteurs