EUROLITE DMX LED Operator 2 controller

Compact DMX controller for easy application

Réf. : 70064502

GTIN: 4026397392289











Description:

The EUROLITE DMX LED Operator 2 is a DMX controller especially designed for the EUROLITE LED-spots and LED-effects with 6 DMX-channels.
This controller features pre-programmed presets and colors, which can easily be displayed by pressing one button. Save your precious time for programming the individual DMX-channels in order to display this color or that color.
Furthermore, you can control one smoke-machine with 2 DMX-channels by pressing a button.

Logistique

EAN / GTIN: 4026397392289
Poids: 1,34 kg
Longueur: 0.36 m
Largeur: 0.21 m
Hauteur: 0.11 m

Caractéristiques:

- 8 control channels only suitable for special LED-spots (RGBA and RGBW)
- Select color mode for choosing single colors
- Internal programs
- Auto mode for running all programs
- Sound-control via built-in microphone
- Pause function
- Blackout function
- Control LEDs display current operating mode
- Program Select-fader for selecting the internal programs
- Speed-fader for adjusting the program-speed
- Strobe-effect with adjustable speed
- Additional fogger button for direct control of a DMX smoke machine (CH-7/8)
- Designed for standing operation, optional installation is customer's choice
- Suitable for 254 mm racks (10") with 4 units
- Power supply via enclosed 12 V DC power unit
- Peut envoyer jusqu'à 8 canaux DMX
- Commandé via DMX; commande de la musique via microphone

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.

- Boîtier du pupitre

Données techniques:

Affectation des broches:	Intérieur + / extérieur -
Puissance totale de raccordement:	4,00 W
Branchement électrique:	Alimentation électrique via fiche creuse (M) version encastrable câble d'alimentation et bloc d'alimentation (inclus dans la livraison) Tramite
Canaux DMX:	Sortie 8
Commande:	DMX; commande de la musique via microphone
Couleur du boîtier:	Noir
Couleur:	Noir
Conception du boîtier:	Boîtier du pupitre
Dimension:	Largeur : 26,5 cm Profondeur : 16,5 cm Hauteur : 5,5 cm
Poids:	1,12 kg
Power supply:	230 V AC, 50 Hz,
	via 12 V DC, 300 mA power unit included in the delivery
DMX512 output:	3-pin XLR connector

Contenu de la livraison:

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® et Dimavery® sont des marques de Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
Tous droits réservés. Sous réserve de modifications techniques et d'erreurs. Toutes les photos sont similaires, les illustrations le sont en partie.