

OMNILUX MR-16 24V/35W GX-5.3 SP 12° EYF

Ampoule pour miroir, lumière froide

Réf. : 91205830

GTIN: 4026397340754



L'article n'est plus disponible.

Caractéristiques:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb)
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh light
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Different illumination angles for different application areas
- Low power consumption
- Long life
- Dimmable
- Inflammable à chaud
- Indice de rendu de couleur (IRC) très élevé

Logistique

EAN / GTIN: 4026397340754

Poids: 0,03 kg

Longueur: 0.04 m

Largeur: 0.04 m

Hauteur: 0.06 m

Données techniques:

Tension nominale (lampes):	24 V, CA
Tension nominale:	35 W
Culot/douille:	GX5,3
Type de lampe:	Lampe halogène
Spécification de l'ampoule:	Dimmable

	Inflammable à chaud
Angle de départ:	12°
Couleur lumineuse:	Blanc
Température de couleur:	2500K
Rendu de couleur (CRI):	95 Ra
Durée de démarrage:	0 s
Construction:	MR-16; réflecteur; culot à broche
Température de fonctionnement max.:	40° C
Température de fonctionnement min.:	20° C
Position de fonctionnement:	S180 (universal)
Durée de vie:	2000 h
Dimensions (LxD):	81x51 mm
Poids:	0,02 kg

Contenu de la livraison: