

## OMNILUX MR-16 24V/35W GX-5.3 SP 38° EYC

Ampoule pour miroir, lumière froide

Réf. : 91205832

GTIN: 4026397343526



### Caractéristiques:

- More light at a same performance by higher coiled filament temperature
- Longer lifetime by permanent filament renewal (tungsten parts bond to the gaseous halogene parts even before reaching the glass bulb)
- The temperature circulation has the effect that the tungsten parts precipitate again on the filament
- Constant light during lifetime, as no bulb blackening occurs
- Comfortable and fresh, white light
- Dimmable (blackening of the glass bulb in case of dimmed operation is eliminated by a short operating time at full voltage)
- Different illumination angles for different application areas
- Low power consumption
- Long lifetime (average lifetime 2000 h)
- Dimmable
- Inflammable à chaud
- Indice de rendu de couleur (IRC) très élevé

### Logistique

EAN / GTIN: 4026397343526

Poids: 0,04 kg

Longueur: 0.04 m

Largeur: 0.04 m

Hauteur: 0.06 m

### Données techniques:

|                             |                |
|-----------------------------|----------------|
| Tension nominale (lampes):  | 24 V, CA       |
| Tension nominale:           | 35 W           |
| Culot/douille:              | GX5,3          |
| Type de lampe:              | Lampe halogène |
| Spécification de l'ampoule: | Dimmable       |

|                                     |                                   |
|-------------------------------------|-----------------------------------|
|                                     | Inflammable à chaud               |
| Angle de départ:                    | 38°                               |
| Couleur lumineuse:                  | Blanc                             |
| Température de couleur:             | 2500K                             |
| Rendu de couleur (CRI):             | 95 Ra                             |
| Durée de démarrage:                 | 0 s                               |
| Construction:                       | MR-16; réflecteur; culot à broche |
| Température de fonctionnement max.: | 40° C                             |
| Température de fonctionnement min.: | 20° C                             |
| Position de fonctionnement:         | S180 (universal)                  |
| Durée de vie:                       | 2000 h                            |
| Dimensions (LxD):                   | 81x51 mm                          |
| Poids:                              | 0,03 kg                           |

**Contenu de la livraison:**