



**The article is no longer in our assortment.**

### Features:

#### EUROLITE STT-400/85 Winch Stand TÜV/GS

High-quality winch-stand, maximum load 85 kg, maximum height 400 cm

- 1-gear winch for easy lifting of the loads
- Automatic braking system
- Safety bolt for mechanical locking
- Easy handling
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height
- TÜV Süd certified
- For application areas such as: Mobile use

#### Package contents

- 1 x user manual

#### EUROLITE TAH-35M Truss Adapter, large

Adapter from 12 - 35 cm, maximum load WLL 300 kg

- Truss adapter for truss systems up to 55 mm diameter
- Adjustable clamps
- Adjustment between 120 mm and 350 mm
- LGA tested

#### Package contents

- 1 x adapter, 2 x bolt, 1 x user manual

#### ALUTRUSS TRILOCK 6082-2000 3-Way Cross Beam

3-point truss system

### Logistic

- Low weight
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

**Package contents**

- 1 x connection Set

**Technical specifications:**

---

Weight:	77,60 kg
---------	----------

---

**EUROLITE STT-400/85 Winch Stand TÜV/GS**

Maximum carrying capacity:	85 kg
----------------------------	-------

---

Minimum load:	25 kg
---------------	-------

---

Standard:	DIN 15560-27, DIN EN ISO 12100-2
-----------	----------------------------------

---

Height:	Maximum: 400 cm above 3 sections Minimum: 175 cm
---------	---

---

Attachment system:	Ø 35mm
--------------------	--------

---

Steel rope:	Ø 4 mm
-------------	--------

---

Type (general stands):	Light stand/wind up
------------------------	---------------------

---

Transport dimensions:	1,75 m x 30 cm x 27 cm
-----------------------	------------------------

---

Base area:	Ø 1,6 m
------------	---------

---

Weight:	24,10 kg
---------	----------

---

**EUROLITE TAH-35M Truss Adapter, large**

Maximum load BGV C1 (8-fold):	150 kg
-------------------------------	--------

---

Max. load WLL (4-fold):	300 kg
-------------------------	--------

---

Width:	Maximum: 35 cm Minimum: 12 cm
--------	----------------------------------

---

Attachment system:	Ø 35mm
--------------------	--------

---

Type (general stands):	Accessory
------------------------	-----------

---

Material:	Steel
-----------	-------

---

Dimensions:	Width: 46 cm Depth: 7,50 cm Height: 22,50 cm
-------------	--

---

Weight:	2,40 kg
---------	---------

---

**ALUTRUSS TRILOCK 6082-2000 3-Way Cross Beam**

Setup:	Easy installation
--------	-------------------

---

Trusspipe:	50 mm x 2 mm
------------	--------------

---

Welding technique:	TIG-welding
--------------------	-------------

---

Welding material:	AlMg 5
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 2 m Width: 29 cm Height: 25,70 cm
Weight:	8,20 kg