



Features:

EUROLITE STT-400/85 Winch Stand TÜV/GS

High-quality winch-stand, maximum load 85 kg, maximum height 400 cm

- 1-gear winch for easy lifting of the loads
- Automatic braking system
- Safety bolt for mechanical locking
- Easy handling
- Complies with DIN 15560-27 and DIN EN ISO 12100-2
- Adjustable height
- TÜV Süd certified

EUROLITE TAH-35M Truss Adapter, large

Adapter from 12 - 35 cm, maximum load WLL 300 kg

- Truss adapter for truss systems up to 55 mm diameter
- Adjustable clamps
- Adjustment between 120 mm and 350 mm
- LGA tested

ALUTRUS TRILOCK 6082-2000 3-way Cross Beam

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified

Logistic

- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	77.60 kg
---------	----------

EUROLITE STT-400/85 Winch Stand TÜV/GS

Maximum carrying capacity:	85 kg
----------------------------	-------

Minimum load:	25 kg
---------------	-------

Standard:	DIN 15560-27, DIN EN ISO 12100-2
-----------	----------------------------------

Height:	Maximum: 400 cm above 3 sections Minimum: 175 cm
---------	---

Attachment system:	Ø 35mm
--------------------	--------

Steel rope:	Ø 4 mm
-------------	--------

Type (general stands):	Light stand/wind up
------------------------	---------------------

Transport dimensions:	175 cm x 30 cm x 27 cm
-----------------------	------------------------

Base area:	Ø 160 cm
------------	----------

Weight:	24.10 kg
---------	----------

EUROLITE TAH-35M Truss Adapter, large

Maximum load BGV C1 (8-fold):	150 kg
-------------------------------	--------

Maximum load WLL (4-fold):	300 kg
----------------------------	--------

Attachment system:	Ø 35mm
--------------------	--------

Type (general stands):	Accessory
------------------------	-----------

Material:	Steel
-----------	-------

Width:	Maximum: 35 cm Minimum: 12 cm
--------	----------------------------------

Dimensions:	Width: 46 cm Depth: 7.50 cm Height: 22.50 cm
-------------	--

Weight:	2.40 kg
---------	---------

ALUTRUSS TRILOCK 6082-2000 3-way Cross Beam

Setup:	Easy installation
--------	-------------------

Trusspipe:	50 mm x 2 mm
------------	--------------

Welding technique:	TIG-welding
--------------------	-------------

Welding material:	AlMg 5
-------------------	--------

Color:	Alu colored
--------	-------------

Strut diameter x thickness:	16 x 2mm
-----------------------------	----------

Dimensions:	Length: 200 cm
-------------	----------------

Width: 29 cm
Height: 25.70 cm

Weight: 8.20 kg

Scope of delivery:

2 x EUROLITE STT-400/85 Winch Stand TÜV/GS

1 x user manual

2 x EUROLITE TAH-35M Truss Adapter, large

1 x adapter
2 x bolt
1 x user manual

3 x ALUTRUSS TRILOCK 6082-2000 3-way Cross Beam

1 x connection set