



### Features:

#### ALUTRUSS Steel Base Plate round type A

Baseplate for mobile use (connectors 6082 included)

- For the vertical installation of truss elements
- Multifunctional use
- High durability
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Trade fair and shop fitting; wedding/gala/events

#### ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

#### ALUTRUSS QUADLOCK End Plate QQGP-Male

### Logistic

- Trusspipe: 50 mm
- Made in Europe  
**cone**
- M8 thread

### EUROLITE LCH-36/55M2 Wall mount for monitors

Wall mount

- Wall mount for LCD monitors with a diagonal screen size of 915 mm (36") to 1400 mm (55")
- Adjustable tilting angle
- Stable metal version
- VESA standard
- Mounting materials included in the delivery

### ALUTRUSS QUICK-LOCK Spare Pivot with Pin

QUICK-LOCK set

- Accessories for the robust truss system with QUICK-LOCK
- For use with TRI/QUAD system
- Trusspipe: 50 mm
- Made in Europe

### Technical specifications:

---

#### ALUTRUSS Steel Base Plate round type A

Trusspipe:	50 mm
Material:	Steel
Color:	Alu colored
Dimensions:	Height: 1.60 cm Diameter: Ø 80 cm
Weight:	60 kg

#### ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Alloy:	AlMgSi1 T6
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 200 cm Width: 29 cm Height: 29 cm
Weight:	10.80 kg

#### ALUTRUSS QUADLOCK End Plate QQGP-Male

Trusspipe:	50 mm
Color:	Alu colored

Weight:	1.45 kg
Thread:	M8 thread

#### **EUROLITE LCH-36/55M2 Wall mount for monitors**

Maximum load BGV C1 (8-fold):	30 kg
Maximum load WLL (4-fold):	60 kg
Distance to wall:	75 mm
Dimensions:	Width: 49.8 cm Depth: 7.5 cm Height: 70 cm
Weight:	5.30 kg
Interface dimensions:	498 x 700 mm
Distance to wall:	75 mm
Dimensions:	748 x 498 x 75 mm

#### **EUROLITE TPC-10 Coupler, silver**

Maximum load BGV C1 (8-fold):	75 kg
Maximum load WLL (4-fold):	150 kg
Tube diameter sector:	48 - 50 mm
Material:	Aluminum
Color:	Silver
Mounting screw:	M10
Dimensions:	Length: 10 cm Width: 3 cm Depth: 9 cm
Weight:	0.16 kg

#### **ALUTRUSS QUICK-LOCK Spare Pivot with Pin**

Trusspipe:	50 mm
Color:	Alu colored
Weight:	0.09 kg

#### **Scope of delivery:**

##### **1 x ALUTRUSS QUADLOCK 6082-2000 4-way Cross Beam**

1 x connection set

##### **4 x ALUTRUSS QUICK-LOCK Spare Pivot with Pin**

2 x splint  
2 x bolt