



**The article is no longer in our assortment.**

---

**Features:****OMNITRONIC MCS-1250 12-channel amplifier**

6-channel audio amplifier with matrix assignment 12 x 50 W/4 ohms

- 12 x 50 W/4 ohms
- Ideal for multi-zone applications
- 6 stereo inputs expandable to 18 stereo zones with further units
- Matrix input assignment: input sources are freely assignable to each channel
- Volume, Treble, Bass adjustment with controller MCS-1250R for each output individually
- Incl. IR remote control
- Incl. 6 controllers MCS-1250R
- Signal inputs via stereo RCA sockets
- Signal outputs via terminal blocks
- Bridged switch for bridging
- LED indicators on the front panel
- Rack installation

**Package contents**

- 1 x remote control

**OMNITRONIC CS-6 Ceiling Speaker white**

6,5" full-range flush-mount speaker, Public address systems 100V, 5 W RMS, Ø 19,5 cm

- For speech and background music in indoor PA systems
- Scratchproof and shockproof
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms
- For further information about this product, please refer to the Data Sheet under "Downloads"

**Package contents**

---

**Logistic**

- 1 x device, 1 x user manual

## Technical specifications:

---

Weight: 23,47 kg

---

### OMNITRONIC MCS-1250 12-channel amplifier

Power supply: 115/230 V AC, 50/60 Hz

---

Power consumption: 1250,00 W

---

Output power: Max. 600 W

---

Frequency range: 20 - 20000 Hz

---

Dimensions: Width: 48,3 cm  
Depth: 42 cm  
Height: 8,9 cm

---

Weight: 11,25 kg

---

Remote control

---

Battery: 2 x Button cell 3.0 V CR2025 lithium manganese built-in

---

Output power sine:

---

Stereo 4 ohms: 12 x 50 W

---

Stereo 8 ohms: 12 x 25 W

---

8 ohms bridged: 6 x 100 W

---

Distortion: 0.01 % (1 kHz)

---

S/N ratio: 85 dB

---

Input sensitivity: 250 mV

---

Input impedance: >47 kohms

---

Zone input connectors: 6 x stereo RCA

---

Link: RS-232

---

Zone output connectors: Terminal blocks

---

Controller connector: RJ45

---

LED indicators (per channel): Signal

---

Dimensions: 482 x 420 x 102 mm

---

### OMNITRONIC CS-6 Ceiling Speaker white

Power: Program: 10W  
Rated: 5W RMS

---

Frequency range: 100 - 10000 Hz

---

Sensitivity: 90 dB (1W/1m)

---

Impedance: Public address systems 100V

---

Power tapping: 1,25W; 2,5W; 5W RMS via Spring terminal switchable

---

Speaker: 1 x woofer 6,5"

---

Type of speaker:	Flush-mount speaker
Material:	ABS Acrylonitrile butadiene styrene
Color:	White, scratchproof and shockproof
Mounting dimensions:	Ø 19,5 cm
Dimensions:	Depth: 7 cm Diameter: Ø 23 cm
Weight:	890 g