



Features:**OMNITRONIC MCS-1250 12-channel amplifier**

6-channel audio amplifier with matrix assignment 12 x 50 W/4 ohms

- 12 x 50 W/4 ohms
- Ideal for multi-zone applications
- 6 stereo inputs expandable to 18 stereo zones with further units
- Matrix input assignment: input sources are freely assignable to each channel
- Volume, Treble, Bass adjustment with controller MCS-1250R for each output individually
- Incl. IR remote control
- Incl. 6 controllers MCS-1250R
- Signal inputs via stereo RCA sockets
- Signal outputs via terminal blocks
- Bridged switch for bridging
- LED indicators on the front panel
- Rack installation

OMNITRONIC CS-6 Ceiling Speaker white

6.5" full-range flush-mount speaker, public address systems 100V, 5 W RMS, Ø 19.5 cm

- For speech and background music in indoor PA systems
- Easy installation
- White metal grille
- Scratchproof and shockproof
- For application areas such as: Installation; restaurants, bars and hotels; sports centres/gyms

Logistic

Technical specifications:

Weight: 23.47 kg

OMNITRONIC MCS-1250 12-channel amplifier

Power supply:	115/230 V AC, 50/60 Hz
Power consumption:	1250.00 W
Output power:	Max. 600 W
Frequency range:	20 - 20000 Hz
Dimensions:	Width: 48.3 cm Depth: 42 cm Height: 8.9 cm
Weight:	11.25 kg
Battery:	2 x button cell 3.0 V CR2025 lithium manganese built-in
Output power sine:	
Stereo 4 ohms:	12 x 50 W
Stereo 8 ohms:	12 x 25 W
8 ohms bridged:	6 x 100 W
Distortion:	0.01 % (1 kHz)
S/N ratio:	85 dB
Input sensitivity:	250 mV
Input impedance:	>47 kohms
Zone input connectors:	6 x stereo RCA
Link:	RS-232
Zone output connectors:	Terminal blocks
Controller connector:	RJ45
LED indicators (per channel):	Signal
Dimensions:	482 x 420 x 102 mm

OMNITRONIC CS-6 Ceiling Speaker white

Power:	Program: 10W Rated: 5W RMS
Frequency range:	100 - 10000 Hz
Sensitivity:	90 dB (1W/1m)
Max. SPL:	100 dB
Impedance:	Public address systems 100V
Setup:	Easy installation
Power tapping:	1.25W; 2.5W; 5W RMS via spring terminal switchable
Speaker:	1 x full range loudspeaker 6.5"

Type of speaker:	Flush-mount speaker
Material:	ABS Acrylonitrile butadiene styrene
Color:	White, scratchproof and shockproof
Mounting dimensions:	Ø 19.5 cm
Dimensions:	Depth: 7 cm Diameter: Ø 23 cm
Weight:	0.89 kg

Scope of delivery:

1 x OMNITRONIC MCS-1250 12-channel amplifier

1 x remote control

12 x OMNITRONIC CS-6 Ceiling Speaker white

1 x device

1 x user manual