



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED PAR-56 COB RGB 100W sil

PRO spotlight as DMX model with COB LED

- Equipped with a powerful RGB 100 W COB LED
- Functions: static colors, RGB color mixture, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Dimmer speed (step response) adjustable
- Operable in stand-alone mode or with DMX interface
- Adjustable microphone sensitivity via LCD display
- Comfortable addressing and setting via control panel with LCD display and four operating buttons
- Locking possibility at the mounting bracket
- With color filter frame
- Ready for connection via power cord with safety-plug
- Available in silver or in black
- 1 powerful LED 100 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
- Strobe effect
- Control via DMX; Sound to light via Microphone
- Preprogrammed in EASY SHOW 1; LED PC-Control 512; Light´J; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
- With a beam angle of 40°
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

#### EUROLITE TB-4X T-Bar

For problem-free installations

- Makes the installation of your lighting system really easy
- Fully wired with DMX-splitter
- 1.50 meters
- With 4 spot connections
- With 4 flap safety-plugs
- With 4 DMX connectors
- Connection via Powercon In/Out-socket

## Technical specifications:

---

Weight:	15,10 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### EUROLITE LED PAR-56 COB RGB 100W sil

Power supply:	230 V AC, 50 Hz
Power consumption:	130 W
IP classification:	IP20
Power connection:	Fixed power supply cord with safety plug
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) 3in1 TCL RGB (homogenous color mix)
DMX channels:	3; 5
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; Sound to light via Microphone
Preprogrammed in:	EASY SHOW 1; LED PC-Control 512; Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	40°
Beam angle (1/2 peak):	40°
Housing color:	Silver
Dimensions:	Width: 24 cm Depth: 36,5 cm Height: 31,5 cm
Weight:	2,6 kg
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### EUROLITE TB-4X T-Bar

Power supply:	230 V AC, 50 Hz
---------------	-----------------

Output current:	Max. 10 A per channel
Dimensions:	Length: 1,5 m Width: 7,5 cm Height: 16,5 cm
Weight:	4,70 kg
Max. power output:	2300 W
Max. total current:	10 A
Max. output/channel:	2300 W
Max. current/channel:	10 A
Maximum load per fixation point:	7.5 kg
Max. spaced braceload:	30 kg
Dimensions (L x W x H):	1500 x 75 x 165 mm