



Features:

EUROLITE LED Pixel Mesh 64x64

Modular LED video panel for indoor use

- Bright and colorful projection of videos, animations and graphics
- Ideal for stage/fair construction and fixed installation
- Modular display concept allows the build-up of large areas
- 40 mm pixel pitch (seamless image at about 40 m)
- 16 x 16 pixels
- Transparent design
- Fast and easy setup
- Ethernet-based signal distribution, IEC inputs and outputs
- Controllable via optional network components and PC software
- For operation per 128 panels (256 x 128 pixels), the optional network interface (80503120) and the network control system consisting of sending card and software LED studio (80503130) is required
- Compatible to media software such as MADRIX
- Matching flightcase available
- Delivery includes 1 x IEC cable, 1 x 50 cm RJ45 cable (80503165), 4 x U-connector (80503150), 4 x gasket (80503152), 4 x bolt (80503154), 1 x eye-bolt
- The device is cooled by passive convection cooling
- For further information about this product, please refer to the Data Sheet under "Downloads"

ROADINGER Flightcase 6x LED Pixel Mesh 64x64

PRO flightcase with castors for 6 x LED Pixel Mesh

- Compartments for 6 LED Pixel Mesh

Logistic

- High-quality workmanship with 9mm plywood multilayered glued, dark brown laminated
- Cover foldable with strap hinge
- Aluminum profile frames (30 mm) with rounded edges
- Three-leg, large steel ball corners (chromium plated)
- 4 castors, 2 of which with locking brakes
- 2 butterfly locks
- 2 hinged, chromium plated case handles
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED Pixel Mesh 64x64

Power supply:	230 V AC, 50 Hz
Power consumption:	75.00 W
IP classification:	IP20
Cooling:	Passive convection cooling
Housing color:	Black
Dimensions:	Width: 64 cm Depth: 6.5 cm Height: 64 cm
Weight:	8.55 kg
Power connector:	IEC input and output
Signal connector:	RJ45
Pixel pitch:	40 mm
Pixel configuration:	2 red, 1 blue, 1 green
Module resolution:	16 x 16
Density (point/m ²):	625
Brightness (cd/m ²):	1300
Scanning mode:	Static
View angle:	120°
Driving voltage:	4.5-5.5 V
Grey scale:	R256 levels, G256 levels, B256 levels
Frame rate:	>/ 60 fps
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 6x LED Pixel Mesh 64x64

Maximum load:	100 kg
Use of brands:	Branded hardware
Dimensions:	Width: 138 cm

Depth: 39 cm
Height: 88 cm

Weight: 40.40 kg

Outside dimensions (L x W x H): 1380 x 390 x 880 mm

Scope of delivery:
